

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cartechnic Cockpit-Spray 300ml

Revision date: 11.02.2019

Product code: 1102678

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Cartechnic Cockpit-Spray 300ml

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Cockpit care

1.3. Details of the supplier of the safety data sheet

Company name: Auto-Teile-Ring GmbH

Street: Otto-Hirsch-Brücken 17

Place: D-70329 Stuttgart

Telephone: + 49 (0) 711/91 89 79-99

Telefax: +49 (0) 711/91 89 79-30

e-mail: info@cartechnic.de

1.4. Emergency telephone number:

111 NHS (National Health Service)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes skin irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics

Signal word: Danger**Pictograms:****Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cartechnic Cockpit-Spray 300ml

Revision date: 11.02.2019

Product code: 1102678

Page 2 of 14

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe Aerosol.
P273	Avoid release to the environment.
P280	Wear protective gloves.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container according to the official regulations.

Special labelling of certain mixtures

EUH208 Contains (R)-p-mentha-1,8-diene; d-limonene. May produce an allergic reaction.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cartechnic Cockpit-Spray 300ml

Revision date: 11.02.2019

Product code: 1102678

Page 3 of 14

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
75-28-5	isobutane			25 - < 50 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas; H220 H280			
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane			25 - < 50 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
64742-49-0	Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics			25 - < 50 %
	927-510-4		01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
74-98-6	propane			10 - < 20 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
106-97-8	butane			0.1 - < 1 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
5989-27-5	(R)-p-mentha-1,8-diene; d-limonene			0.1 - < 1 %
	227-813-5	601-029-00-7		
	Flam. Liq. 3, Skin Irrit. 2, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H226 H315 H317 H400 H410			
75-19-4	cyclopropane			< 0.1 %
	200-847-8	601-016-00-6		
	Flam. Gas 1, Liquefied gas; H220 H280			

Full text of H and EUH statements: see section 16.

Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons, perfumes (Citral).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cartechnic Cockpit-Spray 300ml

Revision date: 11.02.2019

Product code: 1102678

Page 4 of 14

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO₂). Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cartechnic Cockpit-Spray 300ml

Revision date: 11.02.2019

Product code: 1102678

Page 5 of 14

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Observe legal regulations and provisions.

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Protect from frost. Protect against direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane			
Worker DNEL, long-term		inhalation	systemic	2035 mg/m ³
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m ³
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
64742-49-0	Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics			
Worker DNEL, long-term		inhalation	systemic	2085 mg/m ³
Worker DNEL, long-term		dermal	systemic	300 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	447 mg/m ³
Consumer DNEL, long-term		dermal	systemic	149 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	149 mg/kg bw/day

Additional advice on limit values

- a no restriction
- b End of exposure or end of shift
- c at long term exposure: after several previous shifts
- d before next shift

blood (B)
Urine (U)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cartechnic Cockpit-Spray 300ml

Revision date: 11.02.2019

Product code: 1102678

Page 6 of 14

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Protective and hygiene measures

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.

DIN EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time (maximum wearing time) 480min

Thickness of the glove material 0,45 mm

EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	colourless
Odour:	mild

pH-Value (at 20 °C):	not determined	Test method DIN 19268
----------------------	----------------	--------------------------

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	-40 °C
Flash point:	-80 °C

Flammability

Solid:	not applicable
Gas:	not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined

Auto-ignition temperature

Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cartechnic Cockpit-Spray 300ml

Revision date: 11.02.2019

Product code: 1102678

Page 7 of 14

Oxidizing properties

Not oxidising.

Vapour pressure:

not determined

Density (at 20 °C):

0,705 g/cm³ DIN 51757

Water solubility:

The study does not need to be conducted
because the substance is known to be
insoluble in water.

Solubility in other solvents

not determined

Partition coefficient:

not determined

Vapour density:

not determined

Evaporation rate:

not determined

9.2. Other information

Solid content:

not determined

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition productsIncomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.**Further information**

Do not mix with other chemicals.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cartechnic Cockpit-Spray 300ml

Revision date: 11.02.2019

Product code: 1102678

Page 8 of 14

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
75-28-5	isobutane				
	inhalation vapour	LC50 1237 mg/l	Mouse.		
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Study report (1977)	The acute toxicity of SBP 100/140 was de
	inhalation (4 h) vapour	LC50 > 25,2 mg/l	Rat	Study report (1988)	Group of rats were exposed to test subst
64742-49-0	Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics				
	oral	LD50 5500 mg/kg	Rat		
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Study report (1977)	The acute toxicity of SBP 100/140 was de
	inhalation (4 h) vapour	LC50 > 23,3 mg/l	Rat	Study report (1988)	OECD Guideline 403
106-97-8	butane				
	inhalation (4 h) gas	LC50 658 ppm	Rat	GESTIS	
5989-27-5	(R)-p-mentha-1,8-diene; d-limonene				
	oral	LD50 > 5000 mg/kg	Rat	GESTIS	
	dermal	LD50 > 5000 mg/kg	Rabbit	GESTIS	

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Contains (R)-p-mentha-1,8-diene; d-limonene. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane; Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cartechnic Cockpit-Spray 300ml

Revision date: 11.02.2019

Product code: 1102678

Page 9 of 14

The product is not: Ecotoxic.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cartechnic Cockpit-Spray 300ml

Revision date: 11.02.2019

Product code: 1102678

Page 10 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
75-28-5	isobutane					
	Acute fish toxicity	LC50 mg/l	91,42	96 h	Fish, no other information	United States Environmental Protection A The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200 Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200 Calculation using ECOSAR Program v1.00.
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane					
	Acute fish toxicity	LC50 mg/l	> 1-10	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50 mg/l	10 - 30	72 h	Pseudokirchneriella subcapitata	Study report (1995) OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 1-10	48 h	Daphnia magna	
	Fish toxicity	NOEC mg/l	2,045	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010) The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM OECD Guideline 211
64742-49-0	Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics					
	Acute fish toxicity	LC50 mg/l	>1 - 10	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50	12 mg/l	72 h	Pseudokirchneriella subcapitata	SIDS Initial Assessment Report For SIAM OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	>1 - 10	48 h	Daphnia magna	
	Fish toxicity	NOEC mg/l	1,534	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010) The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM OECD Guideline 211
74-98-6	propane					
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200 Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200 Calculation using ECOSAR Program v1.00.
106-97-8	butane					
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A The Ecosar class program has been develo

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cartechnic Cockpit-Spray 300ml

Revision date: 11.02.2019

Product code: 1102678

Page 11 of 14

	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
5989-27-5	(R)-p-mentha-1,8-diene; d-limonene						
	Acute fish toxicity	LC50	0,7 mg/l	96 h	Pimephales promelas		
	Acute crustacea toxicity	EC50 mg/l	0,42	48 h	Daphnia magna		

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane			
	OECD Guideline 301 F	98%	28	
	Easily biodegradable (concerning to the criteria of the OECD)			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	1,09
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	3,4 - 5,2
74-98-6	propane	1,09
106-97-8	butane	1,09
5989-27-5	(R)-p-mentha-1,8-diene; d-limonene	4,23
75-19-4	cyclopropane	1,72

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Waste disposal number of used product

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cartechnic Cockpit-Spray 300ml

Revision date: 11.02.2019

Product code: 1102678

Page 12 of 14

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1
 Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0
 Transport category: 2
 Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1
 Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1
 Marine pollutant: yes
 Special Provisions: 63, 190, 277, 327, 344, 381, 959
 Limited quantity: 1000 mL
 Excepted quantity: E0
 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1
 Special Provisions: A145 A167 A802

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cartechnic Cockpit-Spray 300ml

Revision date: 11.02.2019

Product code: 1102678

Page 13 of 14

Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: isobutane; butane

Entry 29: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane; Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics

2010/75/EU (VOC): No information available.

2004/42/EC (VOC): No information available.

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Aerosol directive (75/324/EEC)

National regulatory information

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits

TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cartechnic Cockpit-Spray 300ml

Revision date: 11.02.2019

Product code: 1102678

Page 14 of 14

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Skin Irrit. 2; H315	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH208	Contains (R)-p-mentha-1,8-diene; d-limonene. May produce an allergic reaction.

Further Information

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]:
Calculation method.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)