

Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

MIEDŹ W SPRAY'U - COPPER GREASE - SPRAY

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: MIEDŹ W SPRAY'U - COPPER GREASE - SPRAY

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Copper spray.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Agencja Handlowa "BOLL" Wojciech Dalewski Spółka Jawna ul. Chemiczna 3 65-713 Zielona Góra - Polska Phone.: 68 451 99 99 - Fax: 68 451 99 00 technolog@boll.pl

1.4 Emergency telephone number:

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aerosol 1: Flammable aerosols, Category 1, H222 Aerosol 1: Pressurised container: May burst if heated., H229 Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411 Skin Irrit. 2: Skin irritation, Category 2, H315 STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger



Hazard statements:

- H222 Extremely flammable aerosol
- H229 Pressurised container: May burst if heated
- H315 Causes skin irritation
- H336 May cause drowsiness or dizziness
- H411 Toxic to aquatic life with long lasting effects

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand

- P102: Keep out of reach of children
- P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P211: Do not spray on an open flame or other ignition source
- P251: Do not pierce or burn, even after use
- P260: Do not breathe spray
- P271: Use only outdoors or in a well-ventilated area
- P273: Avoid release to the environment
- P302+P352: IF ON SKIN: Wash with plenty of water
- P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P403: Store in a well-ventilated place
- P410+P412: Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122°F

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

** Changes with regards to the previous version

** Changes with regards to the previous version



3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: active ingredient mixture with a propellant.

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification		Chemical name/Classification	Concentration
CAS: Non-applicable EC: 921-024-6	Hydrocarbons, C6-C7	r, n-alkanes, isoalkanes, cyclics, <5% n-hexane ⁽¹⁾ Self-classified	
EC: 921-024-6 Index: Non-applicable REACH: 01-2119475514-35-XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336 - Danger	25 - <50 %
CAS: 106-97-8	Butane ⁽¹⁾	ATP CLP00	
EC: 203-448-7 Index: 601-004-00-0 REACH: 01-2119474691-32-XXXX	Regulation 1272/2008	Flam. Gas 1: H220; Press. Gas: H280 - Danger	10 - <25 %
CAS: 74-98-6	Propane ⁽¹⁾	ATP CLP00	
EC: 200-827-9 Index: 601-003-00-5 REACH: 01-2119486944-21-XXXX	Regulation 1272/2008	Flam. Gas 1: H220; Press. Gas: H280 - Danger	10 - <25 %
CAS: 7440-50-8	Miedź [Cu] ⁽¹⁾	Self-classified	
EC: 231-164-3 Index: Non-applicable REACH: Non-applicable	Regulation 1272/2008	Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 2: H411 - Warning	2,5 - <10 %
CAS: 75-28-5	Isobutane ⁽¹⁾	ATP CLP00	
EC: 200-857-2 Index: 601-004-00-0 REACH: 01-2119485395-27-XXXX	Regulation 1272/2008	Flam. Gas 1: H220; Press. Gas: H280 - Danger	2,5 - <10 %
CAS: 61788-45-2	Amines, hydrogenate	ed tallow alkyl ⁽¹⁾ ATP ATP05	
EC: 262-976-6 Index: 612-284-00-9 REACH: 01-2120089693-42-XXXX	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Asp. Tox. 1: H304; Eye Dam. 1: H318; Skin Irrit. 2: H315; STOT RE 2: H373 - Danger	0,025 - <0,1 %

(1) Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 8, 11, 12, 15 and 16.

Other information:

	Id	entification		M-factor
Miedź [Cu]			Acute	10
CAS: 7440-50-8	EC: 231-164-3		Chronic	1
Amines, hydrogenate	d tallow alkyl		Acute	10
CAS: 61788-45-2	EC: 262-976-6		Chronic	10

** Changes with regards to the previous version

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product. By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:



SECTION 4: FIRST AID MEASURES (continued)

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO_2). IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation



SECT	FION 7: HANDLING AND	D STORAGE (continued)		
	spills and residues, de cleanliness where dan	ent legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control estroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and igerous products are used. lations for the prevention of fires and explosions		
	Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,) and transfer at slow speeds to avoid the creation of electrostatic charges. Avoid splashes and pulverizations. Consult section 10 for conditions and materials that should be avoided.			
	C Technical recommend	lations to prevent ergonomic and toxicological risks		
	Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.			
D Technical recommendations to prevent environmental risks				
7.2	 Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity. 7.2 Conditions for safe storage, including any incompatibilities: 			
	A Technical measures for			
	Minimum Temp.:	5 °C		
	Maximum Temp.:	20 °C		
	Maximum time:	24 Months		
	B General conditions for	•		
		, radiation, static electricity and contact with food. For additional information see subsection 10.5		
7.3	Specific end use(s):			

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 **Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace

There are no occupational exposure limits for the substances contained in the product

DNEL (Workers):

		Short e	xposure	Long ex	xposure
Identification		Systemic	Local	Systemic	Local
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	773 mg/kg	Non-applicable
EC: 921-024-6	Inhalation	Non-applicable	Non-applicable	2035 mg/m³	Non-applicable

DNEL (General population):

		Short e	xposure	Long ex	kposure
Identification		Systemic	Local	Systemic	Local
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Oral	Non-applicable	Non-applicable	699 mg/kg	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	699 mg/kg	Non-applicable
EC: 921-024-6	Inhalation	Non-applicable	Non-applicable	608 mg/m ³	Non-applicable

PNEC:

Non-applicable

8.2 **Exposure controls:**

A.- General security and hygiene measures in the work place

Version: 3 (Replaced 2)



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases, vapours and particles		EN 149:2001+A1:2009 EN 405:2001+A1:2009	Replace when an increase in resistence to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420 and EN 374.

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2001 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

, ,				
Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Antistatic and fireproof protective clothing		EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2001 EN ISO 14116:2015 EN 1149-5:2018	Limited protection against flames.
Mandatory foot	Safety footwear with antistatic and heat resistant properties		EN ISO 13287:2012 EN ISO 20345:2011	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	90,01 % weight
V.O.C. density at 20.0C	161 1 kg/m3 (16

V.O.C. density at 20 °C:

464,1 kg/m³ (464,1 g/L)



Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

MIEDŹ W SPRAY'U - COPPER GREASE - SPRAY

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued) Average carbon number: 7 Average molecular weight: 98 g/mol With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics: V.O.C. density at 20 °C: 464,1 kg/m³ (464,1 g/L) EU limit for the product (Cat. B.E): 840 g/L (2010) Components: Non-applicable

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1	Information on basic physical and chemical	properties:
	For complete information see the product datashee	et.
	Appearance:	
	Physical state at 20 °C:	Aerosol
	Appearance:	Fluid
	Colour:	Characteristic
	Odour:	Characteristic
	Odour threshold:	Non-applicable *
	Volatility:	
	Boiling point at atmospheric pressure:	-45 °C (Propellant)
	Vapour pressure at 20 °C:	379969 Pa
	Vapour pressure at 50 °C:	Non-applicable *
	Evaporation rate at 20 °C:	Non-applicable *
	Product description:	
	Density at 20 °C:	714 kg/m³
	Relative density at 20 °C:	0,714
	Dynamic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 40 °C:	Non-applicable *
	Concentration:	Non-applicable *
	pH:	Non-applicable *
	Vapour density at 20 °C:	Non-applicable *
	Partition coefficient n-octanol/water 20 °C:	Non-applicable *
	Solubility in water at 20 °C:	Non-applicable *
	Solubility properties:	Insoluble in water
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Recipient pressure:	Non-applicable *
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Flammability:	
	Flash Point:	-97 °C (Propellant)
	Flammability (solid, gas):	Non-applicable *
	Autoignition temperature:	Non-applicable *
	Lower flammability limit:	0,8 % Volume
	Upper flammability limit: *Not relevant due to the nature of the product, not providing	10.9 % Volume information property of its hazards.
	- CO	NTINUED ON NEXT PAGE -

Revised: 01/04/2019 Version: 3 (Replaced 2)



	Explosive:				
	Lower explosive limit:	Non-applicable *			
	Upper explosive limit:	Non-applicable *			
.2	Other information:				
	Surface tension at 20 °C:	Non-applicable *			
	Refraction index:	Non-applicable *			

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction		Contact with air	Increase in temperature	Sunlight	Humidity
	Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION	11.	ΤΟΥΙΟΟΙ	OCICAL			**
SECTION		TUNICUL	JUGICAL	. INFURI	MATION	

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Castact with the skin and the suce (as the effect).
- C- Contact with the skin and the eyes (acute effect):

** Changes with regards to the previous version



SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
 - IARC: Non-applicable
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
 - Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	A	cute toxicity	Genus
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	LD50 oral	5840 mg/kg	Rat
CAS: Non-applicable	LD50 dermal	2920 mg/kg	Rat
EC: 921-024-6	LC50 inhalation	>20 mg/L (4 h)	
Butane	LD50 oral	>2000 mg/kg	
CAS: 106-97-8	LD50 dermal	>2000 mg/kg	
EC: 203-448-7	LC50 inhalation	658 mg/L (4 h)	Rat
Propane	LD50 oral	>2000 mg/kg	
CAS: 74-98-6	LD50 dermal	>2000 mg/kg	
EC: 200-827-9	LC50 inhalation	>5 mg/L (4 h)	
Miedź [Cu]	LD50 oral	500 mg/kg (ATEi)	
CAS: 7440-50-8	LD50 dermal	>2000 mg/kg	
EC: 231-164-3	LC50 inhalation	>5 mg/L (4 h)	
Isobutane	LD50 oral	>2000 mg/kg	
CAS: 75-28-5	LD50 dermal	>2000 mg/kg	
EC: 200-857-2	LC50 inhalation	>5 mg/L (4 h)	
Amines, hydrogenated tallow alkyl	LD50 oral	>2000 mg/kg	
CAS: 61788-45-2	LD50 dermal	>2000 mg/kg	
EC: 262-976-6	LC50 inhalation	>5 mg/L	

** Changes with regards to the previous version

** Changes with regards to the previous version



	Identification Hydrocarbons, C6-C7, n-alkanes, isoalkanes				Acute toyicity					Genus
		s, cyclics, <5% r)-		Acute toxicity			pecies		
	hexane	-, -, ,	LC30	5.1	mg/L (96 h)		Uncornyr	nchus mykis	S	Fish
	CAS: Non-applicable		EC50		n-applicable					
	EC: 921-024-6		EC50		n-applicable					
	Miedź [Cu]		LC50		- 1 mg/L (96 h)					Fish
	CAS: 7440-50-8		EC50		- 1 mg/L					Crustace
	EC: 231-164-3		EC50		- 1 mg/L					Algae
	Amines, hydrogenated tallow alkyl		LC50		n-applicable		D			
	CAS: 61788-45-2		EC50		3 mg/L (48 h)			nia magna		Crustace
.	EC: 262-976-6		EC50	0.1	2 mg/L (72 h)		Scenedesm	nus subspica	itus	Algae
2.2	Persistence and degradability:									
	Identification		D	egrad	lability		E	Biodegradab	ility	
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes	s, cyclics, <5%	BOD5	r	Non-applicable	Conce	entration		Non-a	pplicable
	n-hexane CAS: Non-applicable		COD	_	Non-applicable	Perio	4		28 day	
	EC: 921-024-6		BOD5/COD	-	Non-applicable		odegradable		20 day 98 %	5
2 3	Bioaccumulative potential:		00007000			70 DIG	acgradable		50 70	
		Identification								
					_		ccumulation	n potent	tial	
	Butane				BC		33			
	CAS: 106-97-8		Pow Log Potential				2.89			
	EC: 203-448-7				_		Moder	ate		
	Propane					BC		13		
	CAS: 74-98-6						v Log	2.86		
	EC: 200-827-9		_	ential -	Low					
	Isobutane CAS: 75-28-5					BC	r v Log	27 2.76		
	EC: 200-857-2						Potential Low			
24	Mobility in soil:					10		Lon		
217	-									
	Identification		-	sorpti	ion/desorption			Volat		
	Butane		Koc		900		Henry			,75 Pa·m³/r
	CAS: 106-97-8		Conclusion		Low		Dry soil		Yes	
	EC: 203-448-7		Surface tensio	n	1,187E-2 N/m (25	°C)	Moist soil		Yes	
	Propane		Koc		460		Henry			,78 Pa•m³/r
	CAS: 74-98-6		Conclusion		Moderate		Dry soil		Yes	
	EC: 200-827-9		Surface tensio	n	7,02E-3 N/m (25 G	(C)	Moist soil		Yes 120576,75 Pa·m ³ /	
	Isobutane CAS: 75-28-5		Koc Conclusion		35 Very High		Henry Dry soil			
	EC: 200-857-2		Surface tensio	n	9,84E-3 N/m (25 G		Moist soil		Yes Yes	
2.5		mont	Surface terisio		5,04E-5 N/III (25	C)	110131 3011		163	
	Product fails to meet PBT/vPvB crite	eria								
2.6	Other adverse effects:									
	Not described									
Chang	es with regards to the previous versio	n								
ECTI	ION 13: DISPOSAL CONSIDERA	ATIONS								

- CONTINUED ON NEXT PAGE -

Version: 3 (Replaced 2)

Revised: 01/04/2019



SECTION 13: DISPOSAL CONSIDERATIONS (continued) 16 05 04* gases in pressure containers (including halons) containing hazardous substances Dangerous Type of waste (Regulation (EU) No 1357/2014): HP3 Flammable, HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage Waste management (disposal and evaluation): Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2. **Regulations related to waste management:** In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014 SECTION 14: TRANSPO Transport of dangerous goods by land: With regard to ADR 2019 and RID 2019: 14.1 UN number: UN1950 14.2 UN proper shipping name: AEROSOLS, flammable 14.3 Transport hazard class(es): 2 Labels: 2.1 14.4 Packing group: N/A

Yes


D

11

190, 327, 344, 625

see section 9

Non-applicable



14.5 Environmental hazards:

14.6 Special precautions for user Special regulations:

Tunnel restriction code:

14.7 Transport in bulk according

Limited quantities:

Physico-Chemical properties:

** Changes with regards to the previous version



SECTION 14: TRANSPORT	INFORMATION ** (continued	
14.1	UN number:	UN1950
14.2	UN proper shipping name:	AEROSOLS, flammable
14.3	Transport hazard class(es):	2
	Labels:	2.1
14.4	Packing group:	N/A
14.5	Environmental hazards:	Yes
14.6	Special precautions for user	
	Physico-Chemical properties:	see section 9
14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable

** Changes with regards to the previous version

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Miedź [Cu] (Product-type 2, 5, 11)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P3a		150	500
E2		200	500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers

Commission Directive 94/1/EC of 6 January 1994 adapting some technicalities of Council Directive 75/324/EEC on the approximation of the laws of the relating Member States to aerosol dispensers

Commission Directive 2008/47/EC of 8 April 2008 amending, for the purposes of adapting to technical progress, Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers

Commission Directive 2013/10/EU of 19 March 2013 amending Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers in order to adapt its labelling provisions to Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures

COMMISSION DIRECTIVE (EU) 2016/2037 of 21 November 2016 amending Council Directive 75/324/EEC as regards the maximum allowable pressure of aerosol dispensers and to adapt its labelling provisions to Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.



CTI	ON 16: OTHER INFORMATION
	Legislation related to safety data sheets:
	This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)
	Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.: COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):
	· New declared substances Butane (106-97-8)
	Isobutane (75-28-5) Propane (74-98-6) CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):
	· Precautionary statements TRANSPORT INFORMATION (SECTION 14):
	· UN number · Packing group
	Texts of the legislative phrases mentioned in section 2: H222: Extremely flammable aerosol
	H315: Causes skin irritation H336: May cause drowsiness or dizziness
	H411: Toxic to aquatic life with long lasting effects H229: Pressurised container: May burst if heated
	Texts of the legislative phrases mentioned in section 3: The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the
	individual components which appear in section 3
	CLP Regulation (EC) No 1272/2008: Acute Tox. 4: H302 - Harmful if swallowed
	Aquatic Acute 1: H400 - Very toxic to aquatic life Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects
	Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways Eye Dam. 1: H318 - Causes serious eye damage
	Flam. Gas 1: H220 - Extremely flammable gas Flam. Liq. 2: H225 - Highly flammable liquid and vapour
	Press. Gas: H280 - Contains gas under pressure, may explode if heated Skin Irrit. 2: H315 - Causes skin irritation STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure
	STOT KE 2: H375 - May cause damage to organis through prolonged of repeated exposure STOT SE 3: H336 - May cause drowsiness or dizziness Classification procedure:
	Aerosol 1: Calculation method
1	Skin Irrit. 2: Calculation method STOT SE 3: Calculation method
	Aquatic Chronic 2: Calculation method Aerosol 1: Calculation method
	Advice related to training: Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their
	comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources:
	http://echa.europa.eu
	http://eur-lex.europa.eu Abbreviations and acronyms:
	ADDreviations and acronyms: ADR: European agreement concerning the international carriage of dangerous goods by road
	IMDG: International maritime dangerous goods code IATA: International Air Transport Association
	ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand
	BOD5: 5-day biochemical oxygen demand BCF: Bioconcentration factor
	LD50: Lethal Dose 50 LC50: Lethal Concentration 50
	EC50: Effective concentration 50 Log-POW: Octanol-water partition coefficient
	Koc: Partition coefficient of organic carbon

- CONTINUED ON NEXT PAGE -

Revised: 01/04/2019

Version: 3 (Replaced 2)



The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -

Version: 3 (Replaced 2)

Revised: 01/04/2019