

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 1-5-2014 Revision date: 18-11-2022 Supersedes: 21-1-2022 Version: 2.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### **1.1. Product identifier**

Product form	
Product name	
Product code	
Product group	

: Mixture : Eurol HPG 80W-90 GL5 LSD : E110634

: Trade product

## **1.2. Relevant identified uses of the substance or mixture and uses advised against**

#### 1.2.1. Relevant identified uses

Intended for general public Main use category Use of the substance/mixture Function or use category

- : Industrial use, professional use, Consumer use
- : Lubricant
- : Lubricants and additives

#### 1.2.2. Uses advised against

No additional information available

## **1.3. Details of the supplier of the safety data sheet**

Eurol bv. B.V. Energiestraat 12 P.O. Box P.O. Box 135 NL– 7442 DA Nijverdal The Netherlands T +31 548 615165 reach@eurol.com - www.eurol.com

### 1.4. Emergency telephone number

Emergency number

: +31 79 3467 808 EVOFENEDEX

#### **SECTION 2: Hazards identification**

## Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

#### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272	2/2008 [CLP]
Precautionary statements (CLP)	: P102 - Keep out of reach of children.
EUH-statements	<ul> <li>EUH208 - Contains 1,3,4-Thiadiazole-2(3H)-thione, 5-(tertdodecyldithio) May produce an allergic reaction.</li> <li>EUH210 - Safety data sheet available on request.</li> </ul>
Child-resistant fastening	: Not applicable
Tactile warning	: Not applicable
2.3. Other hazards	
Other hazards not contributing to the classification	: This product floats on water and may affect the oxygen-balance in the water. The base oil contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT

classified as T/R45: May cause cancer" (Note L).".

Contains no PBT/vPvB substances  $\ge 0.1\%$  assessed in accordance with REACH Annex XIII

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

### SECTION 3: Composition/information on ingredients

## 3.1. Substances

### Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627- 25	≥ 50	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed heavy paraffinic	CAS-No.: 64742-65-0 EC-No.: 265-169-7 REACH-no: 01-2119471299- 27	1 – 3	Asp. Tox. 1, H304
1,3,4-Thiadiazole-2(3H)-thione, 5-(tertdodecyldithio)-	CAS-No.: 73984-93-7 EC-No.: 813-543-0 REACH-no: 01-2119974116- 35	0,1 – 1	Skin Sens. 1B, H317 Aquatic Chronic 3, H412

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general First-aid measures after inhalation	: Seek medical attention if ill effect develops.
First-aid measures after initiation	<ul> <li>Take victim to fresh air, in a quiet place, in an half laying position and if necessary take medical advice. Allow the victim to rest.</li> </ul>
First-aid measures after skin contact	<ul> <li>Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. High-pressure injection under skin may cause serious damage. Seek medical attention if ill effect or irritation develops.</li> </ul>
First-aid measures after eye contact	<ul> <li>Remove contact lenses, if present and easy to do. Continue rinsing. Ensure adequate flushing of eyes by separating eyelids with the fingers. Obtain medical attention if pain, blinking, tears or redness persist.</li> </ul>
First-aid measures after ingestion	: Consult a doctor/medical service if you feel unwell. If vomiting occurs spontaneously, keep head below the hips to prevent aspiration. Do not induce vomiting.
4.2. Most important symptoms and effects,	both acute and delayed
Symptoms/effects after inhalation	: At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
Symptoms/effects after skin contact	: Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis. High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.
Symptoms/effects after eye contact	: Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.
Symptoms/effects after ingestion	<ul> <li>Bad taste. Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea.</li> </ul>
Symptoms/effects upon intravenous administration	: Unknown.

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media Unsuitable extinguishing media	: carbon dioxide (CO2), dry chemical powder, foam. Water fog. : Do not use a heavy water stream. Use of heavy stream of water may spread fire.
5.2. Special hazards arising from the	substance or mixture
Fire hazard Explosion hazard	<ul> <li>Combustion generates: CO, CO2, POx, NOx, SOx, H2S.</li> <li>Not expected to be a fire/explosion hazard under normal conditions of use.</li> </ul>
5.3. Advice for firefighters	
Precautionary measures fire Firefighting instructions Protection during firefighting Other information	<ul> <li>Do not enter fire area without proper protective equipment, including respiratory protection.</li> <li>Use water spray or fog for cooling exposed containers.</li> <li>Use self-contained breathing apparatus and chemically protective clothing.</li> <li>Prevent fire fighting water from entering the environment. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.</li> </ul>

SECTION 6: Accidental release measures	
6.1. Personal precautions, protective e	equipment and emergency procedures
General measures	: Spill area may be slippery. Prevent soil and water pollution. Prevent entry to sewers and public waters.
6.1.1. For non-emergency personnel	
Protective equipment	: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Use protective clothing.
Emergency procedures	: Consider evacuation.
6.1.2. For emergency responders	
Protective equipment	: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
Emergency procedures	: No specific measures are necessary.
6.2. Environmental precautions	

Dike for recovery or absorb with appropriate material. Notify authorities if product enters sewers or public waters. Prevent soil and water pollution. Prevent liquid from entering sewers, watercourses, underground or low areas. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

6.3. Methods and material for co	ntainment and cleaning up
For containment	: Large quantities: Contain large spillage with sand or earth.
Methods for cleaning up	: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Take up large spills with pump or vacuum and finish with dry chemical absorbent.
Other information	: Use suitable disposal containers. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations. On water, recover/skim from surface and pour out in disposal container.

#### 6.4. Reference to other sections

For further information refer to section 13.

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed	: Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.
Precautions for safe handling	<ul> <li>Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled.</li> <li>Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes.</li> </ul>
Hygiene measures	: Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse.
7.2. Conditions for safe storage, inclu	iding any incompatibilities

Technical measures	: Keep container tightly closed and in well ventilated place.
Storage conditions	: Keep only in original container.
Incompatible products	: Reacts vigorously with strong oxidizers and acids.
Maximum storage period	: 5 year
Storage temperature	: ≤ 40 °C
Information on mixed storage	: Keep away from : Oxidizing materials. Strong acids.
Storage area	: Store at ambient temperature.
Special rules on packaging	: Keep container tightly closed and dry.
7.3. Specific end use(s)	

No additional information available

<ul> <li>8.1.1 National occupational exposure and biological limit values</li> <li>No additional information available</li> <li>8.1.2. Recommended monitoring procedures</li> <li>No additional information available</li> <li>8.1.3. Air contaminants formed</li> <li>No additional information available</li> <li>8.1.4. DNEL and PNEC</li> <li>Exposure-value for oil mist : 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours).</li> <li>8.1.5. Control banding</li> <li>No additional information available</li> </ul>	No additional information available 8.1.2. Recommended monitoring procedures No additional information available 8.1.3. Air contaminants formed No additional information available 8.1.4. DNEL and PNEC Exposure-value for oil mist : 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours). 8.1.5. Control banding	8.1. Control parameters	
No additional information available 8.1.3. Air contaminants formed No additional information available 8.1.4. DNEL and PNEC Exposure-value for oil mist : 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours). 8.1.5. Control banding	No additional information available 8.1.3. Air contaminants formed No additional information available 8.1.4. DNEL and PNEC Exposure-value for oil mist : 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours). 8.1.5. Control banding		iological limit values
No additional information available 8.1.4. DNEL and PNEC Exposure-value for oil mist : 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours). 8.1.5. Control banding	No additional information available 8.1.4. DNEL and PNEC Exposure-value for oil mist : 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours). 8.1.5. Control banding		s
Exposure-value for oil mist       : 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours).         8.1.5. Control banding	Exposure-value for oil mist       : 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours).         8.1.5. Control banding		
•			: 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours).
		•	

## 8.2.1. Appropriate engineering controls

### Appropriate engineering controls:

Large quantities: Contain large spillage with sand or earth.

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Gloves. In case of splash hazard: safety glasses. Eye protection should only be necessary where liquid could be splashed or sprayed.

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

#### Eye protection:

Eye protection should only be necessary where liquid could be splashed or sprayed

#### 8.2.2.2. Skin protection

#### Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use. Avoid repeated or prolonged skin contact. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn. Equipment should conform to EN 166.

#### Hand protection:

In case of repeated or prolonged contact wear gloves. The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream). The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

#### Other skin protection

Materials for protective clothing:

PVC gloves. Neoprene or nitrile rubber gloves

### 8.2.2.3. Respiratory protection

#### **Respiratory protection:**

Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn. Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point >65°C) may be required if vapour or abnormal odour is also present due to high product temperature. Use filter type AP or comparable standard.

#### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

See Heading 12. See Heading 6.

#### Consumer exposure controls:

PVC gloves. Neoprene or nitrile rubber gloves.

#### Other information:

Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: brown.
Appearance	: Oily. Liquid.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: ≤ -30 °C
Freezing point	: Not available
Boiling point	: > 280 °C
Flammability	: Not available
Explosive limits	: 0,6 – 7 vol %
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Flash point	: 180 °C
Auto-ignition temperature	: >240 °C
Decomposition temperature	: Not available
рН	: Not available
Viscosity, kinematic	: 250 – 750 mm²/s
Solubility	: insoluble in water.
Log Kow	: Not available
Log Pow	: > 3
Vapour Pressure 20°C	: < 0,1 hPa
Vapour pressure at 50°C	: Not available
Density	: 0,88 – 0,89 kg/l
Relative density	: Not available
Relative vapour density at 20°C	: > 1 (air=1)
Particle characteristics	: Not applicable

## 9.2. Other information

### 9.2.1. Information with regard to physical hazard classes

Explosion limits	: 0,6 – 7 vol %
9.2.2. Other safety characteristics	
Relative evaporation rate (butylacetate=1)	: < 0,1
VOC content	: 0%
Other properties	: Gas/vapour heavier than air at 20°C

SECTION 10: Stability and reactivity
10.1. Reactivity
Stable under normal conditions of use.
10.2. Chemical stability
Stable under normal conditions.
10.3. Possibility of hazardous reactions
Refer to section 10.1 on Reactivity.
10.4. Conditions to avoid
Moisture. Overheating.
10.5. Incompatible materials
Strong oxidizing agents. Strong acids.
10.6. Hazardous decomposition products
No additional information available
SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008		
Acute toxicity (oral) :	Not classified	
Acute toxicity (dermal) :	Not classified	
Acute toxicity (inhalation) :	Not classified	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rat	> 5000 mg/kg	
LC50 Inhalation - Rat	> 5,53 mg/l	

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Eurol HPG 80W-90 GL5 LSD	
Viscosity, kinematic	250 – 750 mm²/s

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

No additional information available

#### 11.2.2. Other information

Other information

: Toxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the toxicology of similar products, Likely route of exposure: ingestion, skin and eye.

SECTION 12: Ecological information		
12.1. Toxicity		
Ecology - water : Hazardous to the aquatic environment, short–term : (acute)	Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. This product floats on water and may affect the oxygen-balance in the water. Not classified Not classified	
Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)	
LC50 fish 1	100 mg/l	
EC50 Daphnia 1	10000 mg/l	
12.2. Persistence and degradability		
Eurol HPG 80W-90 GL5 LSD		
Persistence and degradability Not readily biodegradable.		
12.3. Bioaccumulative potential		
Eurol HPG 80W-90 GL5 LSD		
Log Pow	> 3	
Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.	
12.4. Mobility in soil		
Eurol HPG 80W-90 GL5 LSD		
Ecology - soil	Not miscible with water. Spillages may penetrate the soil causing ground water contamination. This product floats on water and may affect the oxygen-balance in the water.	

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.5. Results of PBT and vPvB assessment	
No additional information available	
12.6. Endocrine disrupting properties	
No additional information available	
12.7. Other adverse effects	
No additional information available	
SECTION 13: Disposal considerations	

13.1. Waste treatment methods	
Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Do not discharge into drains or the environment.
Additional information	: Hazardous waste.
Ecology - waste materials	: Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. When not empty dispose of this container at hazardous or special waste collection point.
European List of Waste (LoW) code	: 13 02 05* - mineral-based non-chlorinated engine, gear and lubricating oils

## **SECTION 14: Transport information**

ADR	IMDG	ΙΑΤΑ	ADN	RID
I4.1. UN number or ID I	number			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shippir	ng name		l	
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard	class(es)		1	
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group			'	
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental ha	zards		l	
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No

14.6. Special precautions for user

**Overland transport** No data available

Transport by sea No data available

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### Air transport

No data available

#### Inland waterway transport

No data available

### **Rail transport**

No data available

#### 14.7. Maritime transport in bulk according to IMO instruments

#### Not applicable

#### **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)	
Applicable on	
Distillates (petroleum), hydrotreated heavy paraffinic ; Distillates (petroleum), solvent-dewaxed heavy paraffinic ; 1,3,4- Thiadiazole-2(3H)-thione, 5-(tertdodecyldithio)-	
1,3,4-Thiadiazole-2(3H)-thione, 5-(tertdodecyldithio)-	

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors) VOC content : 0 %

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No additional information available

#### **SECTION 16: Other information**

Full text of H- and EUH-statements:	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains 1,3,4-Thiadiazole-2(3H)-thione, 5-(tertdodecyldithio) May produce an allergic reaction.
EUH210	Safety data sheet available on request.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.
Skin Sens. 1B	Skin sensitisation, category 1B

Safety Data Sheet (SDS), EU

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.