

SAFETY DATA SHEET of:

Commandant 3

Revision date: Wednesday, July 14, 2021

S101.108

1 SECTION 1: Identification of the substance/mixture and of the company/undertaking:

1.1 Product identifier:

Commandant 3

UFI:

1.2 Relevant identified uses of the substance or mixture and uses advised against:

1

1

Concentration in use: /

1.3 Details of the supplier of the safety data sheet:

Service Best

De Run 4271

5503 LM VELDHOVEN

Phone: +31402302300 — E-mail: dennis.vanherwijnen@servicebest.com — Website: http://www.servicebest.com/

1.4 Emergency telephone number:

+32 70 245 245

2 SECTION 2: Hazards identification:

2.1 Classification of the substance or mixture:

Classification of the substance or mixture in accordance with regulation (EU) 1272/2008:

EUH208 H318 Eye Dam. 1

2.2 Label elements:

Pictograms:



Hazard statements:

EUH208:	Contains (1,2-benzisothiazol-3(2H)-one). May produce an allergic reaction.
H318 Eye Dam. 1:	Causes serious eye damage.
Precautionary statements:	
P280:	Wear protective gloves, protective clothing, eye protection, face protection.
P305+P351+P338:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310:	Immediately call a POISON CENTER or doctor.
Contains:	

Fattyalcohol C12 -14, ethoxylated

2.3 Other hazards:

None

3 SECTION 3: Composition/information on ingredients:

C18-C50 branched, cyclic and linear hydrocarbons - Distillates	≤ 20 %	CAS number:	848301-69-9
		EINECS:	482-220-0
		REACH Registration number:	01-0000020163-82
		CLP Classification:	H304 Asp. Tox. 1
Hydrocarbons, C11-C14, n-alkanes, iso-alkanes,	≤ 10 %	CAS number:	
cyclic, <2% aromatics		EINECS:	926-141-6
		REACH Registration number:	01-2119456620-43
		CLP Classification:	EUH066 H304 Asp. Tox. 1
Fattyalcohol C12 -14, ethoxylated	≤4 %	CAS number:	69011-36-5
		EINECS:	
		REACH Registration number:	
		CLP Classification:	H302 Acute tox. 4 H318 Eye Dam. 1
Methanol	≤2 %	CAS number:	67-56-1
		EINECS:	200-659-6
		REACH Registration number:	01-2119433307-44
		CLP Classification:	H225 Flam. Liq. 2 H301 Acute tox. 3 H311 Acute tox. 3 H331 Acute tox. 3 H370 STOT SE 1
1,2-benzisothiazol-3(2H)-one	≤ 0.008 %	CAS number:	2634-33-5
		EINECS:	220-120-9
		REACH Registration number:	01-2120761540-60
		CLP Classification:	H302 Acute tox. 4 H315 Skin Irrit. 2 H317 Skin Sens. 1A H318 Eye Dam. 1 H400 Aquatic Acute 1

For the full text of the H phrases mentioned in this section, see section 16.

4 SECTION 4: First aid measures:

4.1 Description of first aid measures:

Always ask medical advice as soon as possible should serious or continuous disturbances occur.

Skin contact:	Remove contaminated clothing, rinse skin with plenty of water and immediately transport to hospital.	
Eye contact:	Thoroughly rinse with water (contact lenses to be removed if this is easily done) then take to physician.	
Ingestion:	Rinse mouth, do not induce vomiting, take to hospital immediately.	
Inhalation:	Let sit upright, fresh air, rest and take to hospital.	

4.2 Most important symptoms and effects, both acute and delayed:

Skin contact:	Redness, pain
Eye contact:	Caustic, redness, blurred vision, pain
Ingestion:	Diarrhoea, headache, abdominal cramps, sleepiness, vomiting
Inhalation:	None

4.3 Indication of any immediate medical attention and special treatment needed:

None

5 SECTION 5: Fire-fighting measures:

5.1 Extinguishing media:

CO2, foam, powder, sprayed water

5.2 Special hazards arising from the substance or mixture:

None

5.3 Advice for firefighters:

Extinguishing agents to be None avoided:

6 SECTION 6: Accidental release measures:

6.1 Personal precautions, protective equipment and emergency procedures:

Do not walk into or touch spilled substances and avoid inhalation of fumes, smoke, dusts and vapours by staying up wind. Remove any contaminated clothing and used contaminated protective equipment and dispose of it safely.

6.2 Environmental precautions:

Do not allow to flow into sewers or open water.

6.3 Methods and material for containment and cleaning up:

Contain released substance, store into suitable containers. If possible, remove by using absorbent material.

6.4 Reference to other sections:

For further information, check sections 8 & 13.

7 SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Handle with care to avoid spillage.

7.2 Conditions for safe storage, including any incompatibilities:

Keep in a sealed container in a closed, frost-free, ventilated room.

7.3 Specific end use(s):

1

8 SECTION 8: Exposure controls/personal protection:

8.1 Control parameters:

Listing of the hazardous ingredients in section 3, of which the TLV value is known

Methanol 266 mg/m³

8.2 Exposure controls:

Inhalation protection:	Use with sufficient exhaust ventilation. If necessary, use an air-purifying face mask in case of respiratory hazards. Use the ABEK type as protection against these troublesome levels.	
Skin protection:	Handling with nitril-gloves (EN 374). Breakthrough time: >480' Material thickness: 0,35 mm. Thoroughly check gloves before use. Take of the gloves properly without touching the outside with your bare hands. The manufacturer of the protective gloves has to be consulted about the suitability for a specific work station. Wash and dry your hands.	
Eye protection:	Keep an eye-rinse bottle within reach. Tight-fitting safety goggles. Wear a face shield and protective suit in case of exceptional processing problems.	
Other protection:	Wear impermeable clothing. The type of protective equipment depends on the concentration and amount of hazardous substances at the work station in question.	

9 SECTION 9: Physical and chemical properties:

9.1 Information on basic physical and chemical properties:

Melting point/melting range:	1
Boiling point/Boiling range:	65 °C — 240 °C
pH:	9.5
pH 1% diluted in water:	1
Vapour pressure/20°C,:	12 700 Pa
Vapour density:	Not applicable
Relative density, 20°C:	1.3000 kg/l
Appearance/20°C:	Liquid
Flash point:	65 °C
Flammability (solid, gas):	Not applicable
Auto-ignition temperature:	236 °C
Upper flammability or explosive limit, (Vol %):	36.000 %
Lower flammability or explosive limit, (Vol %):	0.600 %
Explosive properties:	Not applicable

Oxidising properties:	Not applicable
Decomposition temperature:	1
Solubility in water:	Not soluble
Partition coefficient: n- octanol/water:	Not applicable
Odour:	characteristic
Odour threshold:	Not applicable
Dynamic viscosity, 20°C:	10 000 mPa.s
Kinematic viscosity, 40°C:	10 000 mm²/s
Evaporation rate (n-BuAc = 1):	5.900

9.2 Other information:

Volatile organic component (VOC):	15.85 %
Volatile organic component (VOC):	206.009 g/l
Sustained combustion test :	Combustion not sustained

10 SECTION 10: Stability and reactivity:

10.1 Reactivity:

Stable under normal conditions.

10.2 Chemical stability:

Extremely high or low temperatures.

10.3 Possibility of hazardous reactions:

None

10.4 Conditions to avoid:

Protect from sunlight and do not expose to temperatures exceeding + 50°C.

10.5 Incompatible materials:

Acids, alkalines, oxidants, reductants

10.6 Hazardous decomposition products:

Under recommended usage conditions, hazardous decomposition products are not expected.

11 SECTION 11: Toxicological information:

11.1 Information on toxicological effects:

H318 Eye Dam. 1:

Causes serious eye damage.

Calculated acute toxicity, ATE oral:	/
Calculated acute toxicity, ATE	/
dermal:	

C18-C50 branched, cyclic and linear hydrocarbons - Distillates	LD50 oral, rat:	≥ 5 000 mg/kg
nyulocalbons - Distiliates	LD50 dermal, rabbit:	≥ 5 000 mg/kg
	LC50, Inhalation, rat, 4h:	≥ 50 mg/l

Hydrocarbons, C11-C14, n-alkanes, iso- alkanes, cyclic, <2% aromatics	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	≥ 5 000 mg/kg ≥ 5 000 mg/kg ≥ 50 mg/l
Fattyalcohol C12 -14, ethoxylated	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	≥ 5 000 mg/kg ≥ 5 000 mg/kg ≥ 50 mg/l
Methanol	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	143 mg/kg 300 mg/kg 3 mg/l
1,2-benzisothiazol-3(2H)-one	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	500 mg/kg ≥ 5 000 mg/kg ≥ 50 mg/l

12 SECTION 12: Ecological information:

12.1 Toxicity:

Methanol	LC50 (Fish): EC50 (Daphnia): EC50 (Algae):	15400 mg/L (96h) 18260 mg/L (96h) ca. 22000 mg/L (96h)
1,2-benzisothiazol-3(2H)-one	EC50 (Daphnia): NOEC (Daphnia): EC50 (soil microorganisms	16 mg/l (48h) 0.46 mg/l (72h) s): 13 mg/l

12.2 Persistence and degradability:

The surfactants contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

12.3 Bioaccumulative potential:

	Additional data:
Methanol	Log Pow: -0.77

12.4 Mobility in soil:

Water hazard class, WGK (AwSV):	1
Solubility in water:	Not soluble

12.5 Results of PBT and vPvB assessment:

No additional data available

12.6 Other adverse effects:

No additional data available

13 SECTION 13: Disposal considerations:

13.1 Waste treatment methods:

Draining into the sewers is not permitted. Removal should be carried out by licensed services. Possible restrictive regulations by local authority should always be adhered to.

14 SECTION 14: Transport information:

14.1 UN number:

Not applicable

14.2 UN proper shipping name:

ADR, IMDG, ICAO/IATA not applicable

14.3 Transport hazard class(es):

Class(es):	Not applicable
Identification number of the hazard:	Not applicable

14.4 Packing group:

Not applicable

14.5 Environmental hazards:

Not dangerous to the environment

14.6 Special precautions for user:

Hazard characteristics:	Not applicable
Additional guidance:	Not applicable

15 SECTION 15: Regulatory information:

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Water hazard class, WGK (AwSV):	1
Volatile organic component (VOC):	15.847 %
Volatile organic component (VOC):	206.009 g/l
Composition by regulation (EC) 648/2004:	Aliphatic hydrocarbons 5% - 15%, Nonionic surfactants < 5%, Preservatives (Benzisothiazolinone)

15.2 Chemical Safety Assessment:

No data available

16 SECTION 16: Other information:

Legend to abbreviations used in the safety data sheet:

ADR:	The European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE:	Acute Toxicity Estimate	
BCF:	Bioconcentration factor	
CAS:	Chemical Abstracts Service	
CLP:	Classification, Labelling and Packaging of chemicals	
EINECS:	European INventory of Existing commercial Chemical Substances	
LC50:	median Lethal Concentration for 50% of subjects	
LD50:	median Lethal Dose for 50% of subjects	

Nr.:	Number
PTB:	Persistent, Toxic, Bioaccumulative
TLV:	Threshold Limit Value
UFI:	Unique Formula Identifier
vPvB:	very Persistent and very Bioaccumulative substances
WGK:	Water hazard class
WGK 1:	Slightly hazardous for water
WGK 2:	Hazardous for water
WGK 3:	Extremely hazardous for water

Legend to the H Phrases used in the safety data sheet:

EUH066: Repeated exposure may cause skin dryness or cracking. EUH208: Contains (1,2-benzisothiazol-3(2H)-one). May produce an allergic reaction. H225 Flam. Liq. 2: Highly flammable liquid and vapour.
H301 Acute tox. 3: Toxic if swallowed. H302 Acute tox. 4: Harmful if swallowed. H304 Asp. Tox. 1: May be fatal if swallowed and enters airways. H311 Acute tox. 3: Toxic in contact with skin. H315 Skin Irrit. 2: Causes skin irritation. H317 Skin Sens. 1A: May cause an allergic skin reaction. H318 Eye Dam. 1: Causes serious eye damage. H331 Acute tox. 3: Toxic if inhaled. H370 STOT SE 1: Causes damage to organs. H400 Aquatic Acute 1: Very toxic to aquatic life.

CLP Calculation method:

Calculation method

Reason of revision, changes of following items:

Sections: 2.1, 2.2, 3, 9.2, 15.1

SDS reference number:

ECM-112412,00

This safety information sheet has been compiled in accordance with annex II/A of the regulation (EU) No 2015/830. Classification has been calculated in accordance with European regulation 1272/2008 with their respective amendments. It has been compiled with the utmost care. We cannot, however, accept responsibility for damage, of any kind, that may be caused by using these data or the product concerned. To use this preparation for an experiment or a new application , the user must carry out a material suitability and safety study himself.