

Version number 113 Printing date 01.09.2014 Revision: 01.09.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: PROTECTON® LUBRICATING GREASE UNIVERSAL WHITE 400 ML
- · Article number: SER607
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Lubricant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTIP DUPLI B.V.

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel: +31 (0)561 694400

Fax: +31 (0)561 694411

e-mail info@nl.motipdupli.com

- · Further information obtainable from: QHSE Department
- 1.4 Emergency telephone number: +31 629058130 (24 h/d, 7 d/wk)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Flam. Aerosol 1



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2

H315

Causes skin irritation.

STOT SE 3

H336

May cause drowsiness or dizziness.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



F+; Extremely flammable

R12:

Extremely flammable.

N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

(Contd. on page 2)

Printing date 01.09.2014 Version number 113 Revision: 01.09.2014

Trade name: PROTECTON® LUBRICATING GREASE UNIVERSAL WHITE 400 ML

(Contd. of page 1)

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. Warning! Pressurised container.

Has a narcotising effect.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07

GHS09

- · Signal word Danger
- Hazard-determining components of labelling:

pentane

Naphtha (petroleum), hydrotreated light (< 0,1 % benzol CAS nr. 71-43-2)

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P260 Do not breathe spray.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.
- · Dangerous components:

(Contd. on page 3)

Printing date 01.09.2014 Version number 113 Revision: 01.09.2014

Trade name: PROTECTON® LUBRICATING GREASE UNIVERSAL WHITE 400 ML

| | (Co | ontd. of page 2 |
|---|--|-----------------|
| CAS: 109-66-0 EINECS: 203-692-4 Index number: 601-006-00-1 Reg.nr.: 01-2119459286-30-xxxx | pentane Xn R65 F+ R12 N R51/53 R66-67 Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336 | 25-50% |
| CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx | propane ▶ F+ R12 ◆ Flam. Gas 1, H220 Press. Gas, H280 | 12.5-20% |
| CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx | butane F+ R12 Flam. Gas 1, H220 Press. Gas, H280 | 10-12.5% |
| CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx | <i>isobutane F</i> + <i>R12 Flam. Gas 1, H220 Press. Gas, H280</i> | 10-12.5% |
| CAS: 64742-49-0 EC number: 920-750-0 Index number: 649-328-00-1 Reg.nr.: 01-2119475133-43-xxxx | F R11 N R51/53 R67 Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336 | 10-12.5% |
| CAS: 6869-42-3 EINECS: 272-028-3 | Zinc alkyldithiophosphate Xi R38-41 N R51/53 Eye Dam. 1, H318 Aquatic Chronic 2, H411 Skin Irrit. 2, H315 | 0.1-1% |

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

· Additional information: For the wording of the listed risk phrases refer to section 16.

GB

Printing date 01.09.2014 Version number 113 Revision: 01.09.2014

Trade name: PROTECTON® LUBRICATING GREASE UNIVERSAL WHITE 400 ML

(Contd. of page 3)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

109-66-0 pentane

WEL Long-term value: 1800 mg/m³, 600 ppm

(Contd. on page 5)

Printing date 01.09.2014 Version number 113 Revision: 01.09.2014

Trade name: PROTECTON® LUBRICATING GREASE UNIVERSAL WHITE 400 ML

(Contd. of page 4)

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

- · Respiratory protection: Not required.
- · Protection of hands: Not required.
- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- · Eye protection: Not required.

| SECTION 9: | ו יות | | • • | , | • |
|--------------|----------|-----|--------------|---------|---------|
| NEL TITON U. | Physical | ana | сиомиса | nvanavt | 100 |
| | | | 914911149111 | | 4 -70 1 |

| 9.1 Information on basic physical an General Information | a cnemicai properties | |
|---|---|--|
| · Appearance: | | |
| Form: | Aerosol | |
| Colour: | According to product specification | |
| Odour: | Characteristic | |
| Odour threshold: | Not determined. | |
| pH-value: | Not determined. | |
| Change in condition | | |
| Melting point/Melting range: | Undetermined. | |
| Boiling point/Boiling range: | Not applicable, as aerosol. | |
| Flash point: | < 0 °C (< 32 °F) | |
| | Not applicable, as aerosol. | |
| Flammability (solid, gaseous): | Not applicable. | |
| Ignition temperature: | > 200 °C (> 392 °F) | |
| Decomposition temperature: | Not determined. | |
| Self-igniting: | Product is not selfigniting. | |
| Danger of explosion: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. | |
| Explosion limits: | | |
| Lower: | 0.6 Vol % | |
| Upper: | 10.9 Vol % | |
| Vapour pressure at 20 °C (68 °F): | 3500 hPa (2625 mm Hg) | |
| Density at 20 °C (68 °F): | 0.672 g/cm³ (5.608 lbs/gal) | |
| Relative density | Not determined. | |
| Vapour density | Not determined. | |
| Evaporation rate | Not applicable. | |
| Solubility in / Miscibility with | | |
| water: | Not miscible or difficult to mix. | |
| Partition coefficient (n-octanol/water | r): Not determined. | |

(Contd. on page 6)

Printing date 01.09.2014 Version number 113 Revision: 01.09.2014

Trade name: PROTECTON® LUBRICATING GREASE UNIVERSAL WHITE 400 ML

(Contd. of page 5)

Viscosity:
Dynamic:
Kinematic:
Not determined.
Not determined.

· Solvent content:

 Organic solvents:
 74.0 %

 • EU-VOC:
 497.3 g/l

 • EU-VOC in %:
 74.00 %

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

| LD/LC50 values relevant for classification: | | | |
|---|---|----------------------|--|
| 109-66-0 р | 109-66-0 pentane | | |
| Oral | Oral LD50 >16000 mg/kg (rat) | | |
| Dermal | mal LD50 >2500 mg/kg (rat) | | |
| | | >5000 mg/kg (rabbit) | |
| Inhalative | Inhalative LC50 / 4 h >100 mg/m3 (rat) | | |
| 106-97-8 b | 106-97-8 butane | | |
| Inhalative | Inhalative LC50 / 4 h 658000 mg/m3 (rat) | | |
| 64742-49- | 64742-49-0 Naphtha (petroleum), hydrotreated light (< 0,1 % benzol CAS nr. 71-43-2) | | |
| Oral | LD50 | >5000 mg/kg (rat) | |
| Dermal | LD50 | >2600 mg/kg (rabbit) | |
| Inhalative | LC50 / 4 h | >193 mg/m3 (rat) | |

- · Primary irritant effect:
- · on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitisation: No sensitising effects known.

SECTION 12: Ecological information

· 12.1 Toxicity

| · Aquatic toxicity: | | |
|---|--------------------------------------|--|
| 109-66-0 pentane | | |
| EC50 / 48 h | 9.7 mg/l (daphnia magna) | |
| LC50 / 96 h | 1-10 mg/l (fish) | |
| 64742-49-0 Naphtha (petroleum), hydrotreated light (< 0,1 % benzol CAS nr. 71-43-2) | | |
| LC50 | LC50 127-159 mg/l (Leuciscus idus) | |

(Contd. on page 7)

Printing date 01.09.2014 Version number 113 Revision: 01.09.2014

Trade name: PROTECTON® LUBRICATING GREASE UNIVERSAL WHITE 400 ML

(Contd. of page 6)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

| · European | · European waste catalogue | | | |
|------------|----------------------------|--|--|--|
| 20 01 13* | solvents | | | |
| 15 01 04 | metallic packaging | | | |

- · Uncleaned packaging:
- · Recommendation: Non contaminated packagings may be recycled.

SECTION 14: Transport information

| · 14.1 UN-Number · ADR, IMDG, IATA | UN1950 |
|---|---|
| · 14.2 UN proper shipping name · ADR · IMDG · IATA | 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS AEROSOLS AEROSOLS, flammable |
| 142 T | |

- · 14.3 Transport hazard class(es)
- $\cdot ADR$



· Class
 · Label
 2 5F Gases.
 2.1

· IMDG, IATA



• Class • Label 2.1

(Contd. on page 8)

Printing date 01.09.2014 Version number 113 Revision: 01.09.2014

Trade name: PROTECTON® LUBRICATING GREASE UNIVERSAL WHITE 400 ML

| | (Contd. of page |
|--|--|
| · 14.4 Packing group · ADR, IMDG, IATA | Void |
| · 14.5 Environmental hazards: | Product contains environmentally hazardous substances: pentane |
| · Marine pollutant: | No |
| · 14.6 Special precautions for user · Danger code (Kemler): | Warning: Gases. |
| · EMS Number: | F-D,S-U |
| · 14.7 Transport in bulk according to Anne MARPOL73/78 and the IBC Code | ex II of Not applicable. |
| · Transport/Additional information: | |
| · ADR | |
| · Limited quantities (LQ) | 1L |
| · Excepted quantities (EQ) | Code: E0 |
| | Not permitted as Excepted Quantity |
| · Transport category | 2 |
| · Tunnel restriction code | D |
| · <i>IMDG</i> | |
| · Limited quantities (LQ) | IL |
| · Excepted quantities (EQ) | Code: E0 |
| | Not permitted as Excepted Quantity |
| · UN "Model Regulation": | UN1950, AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS |

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- R11 Highly flammable.
- R12 Extremely flammable.
- R38 Irritating to skin.
- R41 Risk of serious damage to eyes.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- *R65* Harmful: may cause lung damage if swallowed.
- *R66* Repeated exposure may cause skin dryness or cracking.
- *R67* Vapours may cause drowsiness and dizziness.

(Contd. on page 9)

Printing date 01.09.2014 Version number 113 Revision: 01.09.2014

Trade name: PROTECTON® LUBRICATING GREASE UNIVERSAL WHITE 400 ML

(Contd. of page 8)

· Department issuing MSDS: QHSE Department

· Contact: Mr. K. Smedeman

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas: Gases under pressure: Compressed gas

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

* Data compared to the previous version altered.

CD