

Printing date 20.10.2015 Version number 67 Revision: 15.10.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: PROTECTON® VASELINE SPRAY 400 ML
- · Article number: SER9710
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC24 Lubricants, greases, release products
- · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

· Environmental release category

ERC8a Wide dispersive indoor use of processing aids in open systems

ERC8d Wide dispersive outdoor use of processing aids in open systems

- · Application of the substance / the mixture Preparation
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTIP DUPLI B.V.

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel: +31 (0)561 694400 Fax: +31 (0)561 694411 e-mail info@nl.motipdupli.com

- · Further information obtainable from: Department Product Safety
- 1.4 Emergency telephone number: +31 (0)561-694400 (09:00h 17:00h)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 20.10.2015 Version number 67 Revision: 15.10.2015

Trade name: PROTECTON® VASELINE SPRAY 400 ML

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

pentane

propan-2-ol

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P260 Do not breathe spray.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

CAS: 109-66-0	pentane	20-25%
EINECS: 203-692-4	Flam. Liq. 2, H225	
Index number: 601-006-00-1	3 Asp. Tox. 1, H304	
Reg.nr.: 01-2119459286-30-xxxx	Aquatic Chronic 2, H411	
	♦ STOT SE 3, H336	
CAS: 64742-48-9	Naphta (petroleum), hydrotreated heavy	12.5-20%
EC number: 918-481-9	& Asp. Tox. 1, H304	
Reg.nr.: 01-2119457273-39-xxxx		
CAS: 74-98-6	propane	12.5-20%
EINECS: 200-827-9	♦ Flam. Gas 1, H220	
Index number: 601-003-00-5	Press. Gas C, H280	
Reg.nr.: 01-2119486944-21-xxxx		
CAS: 106-97-8	butane	10-12.5%
EINECS: 203-448-7	(b) Flam. Gas 1, H220	
Index number: 601-004-00-0	Press. Gas C, H280	
Reg.nr.: 01-2119474691-32-xxxx		

u. on page .

(Contd. of page 1)

Printing date 20.10.2015 Version number 67 Revision: 15.10.2015

Trade name: PROTECTON® VASELINE SPRAY 400 ML

	(Co	ontd. of page 2)
CAS: 67-63-0	propan-2-ol	10-12.5%
EINECS: 200-661-7	◈ Flam. Liq. 2, H225	
Index number: 603-117-00-0	Eye Irrit. 2, H319; STOT SE 3, H336	
Reg.nr.: 01-2119457558-25-xxxx	•	
CAS: 75-28-5	isobutane	5-10%
EINECS: 200-857-2	♦ Flam. Gas 1, H220	
Index number: 601-004-00-0	Press. Gas C, H280	
Reg.nr.: 01-2119485395-27-xxxx		

• Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- · 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)

Printing date 20.10.2015 Version number 67 Revision: 15.10.2015

Trade name: PROTECTON® VASELINE SPRAY 400 ML

(Contd. of page 3)

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

7 1.	.,1 1,	1 11 1	• •,	• 4.1	1 1
· Ingredients	with limit v	values that r	eauire monita	oring at the	workplace:

109-66-0 pentane

WEL Long-term value: 1800 mg/m³, 600 ppm

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm

Long-term value: 1430 mg/m², 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

- · Respiratory protection: Not required.
- · Protection of hands: Not required.
- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- · Eye protection: Not required.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Appearance:

Form: Aerosol

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

(Contd. on page 5)

Printing date 20.10.2015 Version number 67 Revision: 15.10.2015

Trade name: PROTECTON® VASELINE SPRAY 400 ML

	(Contd. of page
· Flash point:	$<0~^{\circ}C~(<32~^{\circ}F)$ Not applicable, as aerosol.
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	> 200 °C (> 392 °F)
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	0.6 Vol %
Upper:	12.0 Vol %
· Vapour pressure at 20 °C (68 °F):	3500 hPa (2625 mm Hg)
Density at 20 °C (68 °F):	$0.65592 \ g/cm^3 (5.474 \ lbs/gal)$
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	r): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	85.0 %
· EU-VOC:	557.5 g/l
· EU-VOC in %:	85.00 %
· Solids content:	15.0 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

· LD/LC50	· LD/LC50 values relevant for classification:				
109-66-0	pentane				
Oral	LD50	>16000 mg/kg (rat)			
Dermal	LD50	>2500 mg/kg (rat)			

(Contd. on page 6)

Printing date 20.10.2015 Version number 67 Revision: 15.10.2015

Trade name: PROTECTON® VASELINE SPRAY 400 ML

		(Contd. of page 5	
		>5000 mg/kg (rabbit)	
Inhalative	LC50 / 4 h	>100 mg/m3 (rat)	
64742-48-	9 Naphta (p	etroleum), hydrotreated heavy	
Oral	LD50	>15000 mg/kg (rat)	
Dermal	<i>LD50</i>	>3000 mg/kg (rab)	
Inhalative	LC50 / 4 h	>2.8 mg/m3 (rat)	
8009-03-8	8009-03-8 Petrolatum		
Oral	LD50	>5000 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rabbit)	
106-97-8 b	utane		
Inhalative	LC50 / 4 h	658000 mg/m3 (rat)	
67-63-0 pr	67-63-0 propan-2-ol		
Oral	LD50	5045 mg/kg (rat)	
Dermal	<i>LD50</i>	12800 mg/kg (rabbit)	
	LC50 / 4 h	30 mg/m3 (rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:			
109-66-0 pentane			
EC50 / 48 h	9.7 mg/l (daphnia magna)		
LC50 / 96 h	1-10 mg/l (fish)		
64742-48-9 Naphta (p	64742-48-9 Naphta (petroleum), hydrotreated heavy		
LC50 / 96 h	>100 mg/l (crustacean (amphipod))		
	>100 mg/l (fish)		
67-63-0 propan-2-ol			
EC50 / 48 h	13299 mg/l (daphnia magna)		
LC50 / 96 h (dynamic)	4200 mg/l (fish)		

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 7)

Printing date 20.10.2015 Version number 67 Revision: 15.10.2015

Trade name: PROTECTON® VASELINE SPRAY 400 ML

(Contd. of page 6)

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European	waste catalogue
14 06 03*	other solvents and solvent mixtures
15 01 04	metallic packaging

- · Uncleaned packaging:
- · Recommendation: Non contaminated packagings may be recycled.

14.1 UN-Number		
ADR, IMDG, IATA	UN1950	
14.2 UN proper shipping name		
ADR	1950 AEROSOLS	
IMDG	AEROSOLS	
IATA	AEROSOLS, flammable	
14.3 Transport hazard class(es)		
ADR		
Class	2 5F Gases.	
Label	2.1	
IMDG, IATA		
Class	2.1	
Label	2.1	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Warning: Gases.	
Danger code (Kemler):	- -	
EMS Number:	F- D , S - U	

-GB

Printing date 20.10.2015 Version number 67 Revision: 15.10.2015

Trade name: PROTECTON® VASELINE SPRAY 400 ML

	(Contd.	of page
· 14.7 Transport in bulk according to Anna	ex II of	
Marpol and the IBC Code	Not applicable.	
· Transport/Additional information:		
· ADR		
· Limited quantities (LQ)	IL	
· Excepted quantities (EQ)	Code: E0	
	Not permitted as Excepted Quantity	
· Transport category	2	
· Tunnel restriction code	D	
· IMDG		
· Limited quantities (LQ)	1L	
· Excepted quantities (EQ)	Code: E0	
	Not permitted as Excepted Quantity	
· UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

- · Department issuing MSDS: R&D legislation and regulatory advisor
- · Contact: Mr. K. Smedeman
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases, Hazard Category 1

(Contd. on page 9)

Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.10.2015 Version number 67 Revision: 15.10.2015

Trade name: PROTECTON® VASELINE SPRAY 400 ML

(Contd. of page 8)

Aerosol 1: Flammable aerosols, Hazard Category 1 Press. Gas C: Gases under pressure: Compressed gas Flam. Liq. 2: Flammable liquids, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

* Data compared to the previous version altered.