

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Gear oil 75W - 80
Article number: 180073

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Gearbox oil

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG
Wilhelmstr. 47
58256 Ennepetal / GERMANY
Phone +49 2333 911-0
Fax +49 2333 911-444
Homepage www.febi.com
E-mail info@febi.com

Address enquiries to

Technical information info@febi.com
Safety Data Sheet info@febi.com

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (GB) CLP]

No classification.

2.2 Label elements

The product is required to be labelled in accordance with regulation CLP.

Hazard pictograms none

Signal word none

Hazard statements none

Special labelling EUH210 Safety data sheet available on request.

Contains: 3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid. EUH208 May produce an allergic reaction.

2.3 Other hazards

Environmental hazards Does not contain any PBT or vPvB substances.
Contains no ingredients with endocrine-disrupting properties.

Other hazards No particular hazards known.

SECTION 3: Composition / Information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
1 - < 10	Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt)
	CAS: 64742-65-0, EINECS/ELINCS: 265-169-7, Reg-No.: 01-2119471299-27-XXXX
	GHS/CLP: Asp. Tox. 1: H304
0,1 - < 0,93	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)
	EINECS/ELINCS: 931-384-6, Reg-No.: 01-2119493620-38
	GHS/CLP: Acute Tox. 4: H302 - Eye Dam. 1: H318 - Skin Sens. 1: H317 - Aquatic Chronic 2: H411
	SCL [%]: > 50: Eye Irrit. 2: H319, >= 9,39: Skin Sens. 1B: H317, > 50: Eye Dam. 1: H318
0,1 - 1	3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid
	CAS: 268567-32-4, EINECS/ELINCS: 434-070-2, Reg-No.: 01-2119658068-31
	GHS/CLP: Eye Dam. 1: H318 - Skin Sens. 1B: H317 - Aquatic Chronic 3: H412

Comment on component parts

For full text of H-statements: see SECTION 16.
Contains less than 3% w/w DMSO-extract (only for mineral oils)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Change soaked clothing.

Inhalation

Ensure supply of fresh air.
In the event of symptoms seek medical treatment.

Skin contact

In case of contact with skin wash off immediately with soap and water.
Consult a doctor if skin irritation persists.

Eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.

Ingestion

Do not induce vomiting.
Consult a doctor immediately.
Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

Headache

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
Forward this sheet to your doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam, dry powder, water spray jet, carbon dioxide.

Extinguishing media that must not be used

Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.
Carbon monoxide (CO)
Sulphur oxides (SOx).
Nitrogen oxides (NOx).

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.
Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Some risk of slipping due to spillage of product.
Forms slippery surfaces with water.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. oil binder).
Dispose of absorbed material in accordance with the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

No special measures necessary if used correctly.
Use only in well-ventilated areas.
Use solvent-resistant equipment.

The product is combustible.

Do not eat, drink or smoke when using this product.
After worktime and before work breaks the affected skin areas must be thoroughly cleaned.
Use barrier skin cream.
Contaminated work clothing should not be allowed out of the workplace.
Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.
Prevent penetration into the ground.
Do not store together with oxidizing agents.
Keep container in a well-ventilated place.
Keep container tightly closed.

7.3 Specific end use(s)

See product use, SECTION 1.2

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (UK)

not relevant

Ingredients with occupational exposure limits to be monitored EU (2004/37/EG)

not relevant

DNEL

Substance
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4
Industrial, inhalative, Long-term - systemic effects, 4,4 mg/m ³ (AF=25)
Industrial, dermal, Long-term - systemic effects, 1.25 mg/kg bw/d (AF=100)
general population, inhalative, Long-term - systemic effects, 1.1 mg/m ³ (AF=50)
general population, dermal, Long-term - systemic effects, 0.6 mg/kg bw/d (AF=200)
general population, oral, Long-term - systemic effects, 0.6 mg/kg bw/d (AF=200)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
Industrial, inhalative, Long-term - systemic effects, 2,73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5,58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 970 µg/kg bw/day
general population, oral, Long-term - local effects, 740 µg/kg bw/day
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)
Industrial, inhalative, Long-term - systemic effects, 4.28 mg/m ³ (AF=30)
Industrial, dermal, Long-term - systemic effects, 12.5 mg/kg bw/d (AF=120)
general population, dermal, Long-term - systemic effects, 6.25 mg/kg bw/d (AF=240)
general population, oral, Long-term - systemic effects, 0.25 mg/kg bw/d (AF=600)
general population, inhalative, Long-term - systemic effects, 1.09 mg/m ³ (AF=60)

PNEC

Substance
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4
freshwater, 0.072 mg/L (AF=50)
seawater, 0.007 mg/L (AF=500)
sewage treatment plants (STP), 10 mg/l (AF=10)
sediment (freshwater), 23 mg/kg dw
sediment (seawater), 2.3 mg/kg dw
soil, 4.54 mg/kg dw
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
oral (food), 9,33 mg/kg food
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)
freshwater, 2.4 µg/L (AF=50)
seawater, 0.24 µg/L (AF=500)
sewage treatment plants (STP), 24.33 mg/L (AF=100)
sediment (freshwater), 12.9 µg/kg dw
sediment (seawater), 1.29 µg/kg dw
soil, 1.17 µg/kg dw
oral (food), 10 mg/kg dw (AF=300)

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.
Eye protection	Safety glasses. (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. > 0,4 mm: Nitrile rubber, >120 min (EN 374-1/-2/-3).
Skin protection	Light protective clothing.
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin.
Respiratory protection	not applicable
Thermal hazards	No information available.
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Form	liquid
Color	yellowish
Odor	characteristic
Odour threshold	No information available.
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point or initial boiling point and boiling range [°C]	not applicable
Flash point [°C]	241
Flammability	Not explosive.
Lower explosion limit	not self-igniting
Upper explosion limit	not applicable
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	No information available.
Density [g/cm³]	0,85 (20 °C / 68,0 °F)
Relative density	not determined
Bulk density [kg/m³]	not applicable
Solubility in water	immiscible
Solubility other solvents	No information available.
Partition coefficient n-octanol/water (log value)	No information available.
Kinematic viscosity	56 mm ² /s 40°C (DIN 51562)
Relative vapour density	No information available.
Melting point [°C]	No information available.
Auto-ignition temperature [°C]	not applicable
Decomposition temperature [°C]	No information available.
Particle characteristics	No information available.

9.2 Other information

No information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

See SECTION 10.3.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

Reactions with strong alkalis.

Reactions with strong acids.

10.4 Conditions to avoid

Strong heating.

10.5 Incompatible materials

Strong oxidizing agent.

See SECTION 10.3.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

Substance
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4
LD50, oral, Rat, > 2000 mg/kg bw
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
LD50, oral, Rat, 5000 mg/kg bw
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)
LD50, oral, Rat, 2000 mg/kg

Acute dermal toxicity

Substance
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4
LD50, dermal, Rat, > 2000 mg/kg bw
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
LD50, dermal, Rabbit, > 2000 - 5000 mg/kg bw

Acute inhalational toxicity

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
LC50, inhalative, Rat, 2,18 - 5,53 mg/L air 4h, 4h

Serious eye damage/irritation

Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
Eye, non-irritating

Skin corrosion/irritation

Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
dermal, non-irritating

Respiratory or skin sensitisation

Based on the available information, the classification criteria are not fulfilled.
May produce an allergic reaction.
Calculation method

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
dermal, non-sensitizing

Specific target organ toxicity — single exposure

Based on the available information, the classification criteria are not fulfilled.

Specific target organ toxicity — repeated exposure

Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
NOAEL, inhalative, Rat, 980 mg/m ³ air, no adverse effect observed
LOAEL, dermal, mouse, 100 mg/kg bw/day, The effects observed are not sufficient for classification.

LOAEL, oral, Rat, 125 mg/kg bw/day, The effects observed are not sufficient for classification.

Mutagenicity Based on the available information, the classification criteria are not fulfilled.

Substance

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

in vitro, negativ

Reproduction toxicity Based on the available information, the classification criteria are not fulfilled.

- Fertility

Substance

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

NOAEL, oral, Rat, 1000 mg/kg bw/d, no adverse effect observed

- Development No information available.

Carcinogenicity Based on the available information, the classification criteria are not fulfilled.

Aspiration hazard Based on the available information, the classification criteria are not fulfilled.

General remarks

The toxicological data are those of the pure product.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties Contains no ingredients with endocrine-disrupting properties.

11.2.2 Other information none

SECTION 12: Ecological information

12.1 Toxicity

Substance

3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4

LC50, (96h), fish, 54 mg/l

EC50, (48h), Daphnia magna, 53 mg/l

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

NOELR, (14d), fish, 1 g/L

LL50, (96h), Invertebrates, 10 g/L

LL50, (96h), fish, 100 mg/L

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

LC50, (96h), fish, 24 mg/l

EC50, (48h), Daphnia magna, 91,4 mg/l

12.2 Persistence and degradability

Behaviour in environment compartments not determined

Behaviour in sewage plant not determined

Biological degradability not determined

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

12.7 Other adverse effects

Ecological data of complete product are not available.

Do not discharge product unmonitored into the environment or into the drainage.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

In according to RoHS!
Disposal in an incineration plant in accordance with the regulations of the local authorities.

Waste no. (recommended)

130205* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.
Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended)

150110* packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

Ferdinand Bilstein GmbH + Co. KG

Date printed 23.04.2024, Revision 23.04.2024

Version 3.0. Supersedes version: 2.0 Page 10 / 12

14.2 UN proper shipping name

Transport by land according to ADR/RID	NO DANGEROUS GOODS
Inland navigation (ADN)	NO DANGEROUS GOODS
Marine transport in accordance with IMDG	NOT CLASSIFIED AS "DANGEROUS GOODS"
Air transport in accordance with IATA	NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

Transport by land according to ADR/RID	not applicable
Inland navigation (ADN)	not applicable
Marine transport in accordance with IMDG	not applicable
Air transport in accordance with IATA	not applicable

14.4 Packing group

Transport by land according to ADR/RID	not applicable
Inland navigation (ADN)	not applicable
Marine transport in accordance with IMDG	not applicable
Air transport in accordance with IATA	not applicable

14.5 Environmental hazards

Transport by land according to ADR/RID	no
Inland navigation (ADN)	no
Marine transport in accordance with IMDG	no
Air transport in accordance with IATA	no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS	2008/98/EG (2000/532/EC); 2010/75/EU; 2004/42/EG; (EG) 648/2004; (EC) 1907/2006 (REACH); (EU) 1272/2008; 75/324/EWG ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131; (EU) 517/2014; (EU) 2019/1148; (EU) 2019/1021, (EU) 2023/707
- Comment on component parts	Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
- Annex I (REACH)	The product is not subject to Annex I restrictions.
- Annex XIV (REACH)	According to Annex XIV of Regulation (EC) 1907/2006 (REACH) the product does not contain any substances \geq 0.1% that are subject to authorisation.
- Annex XVII (REACH)	According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product contains \geq 0.1% of substances with the following restrictions. 75 According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product is not subject to any restrictions.
TRANSPORT-REGULATIONS	ADR (2023); IMDG-Code (2023, 41. Amdt.); IATA-DGR (2024)
NATIONAL REGULATIONS (UK):	EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK REACH; GB CLP.
- Observe employment restrictions for people	Observe employment restrictions for mothers-to-be and nursing mothers. Observe employment restrictions for young people.
- VOC (2010/75/CE)	not relevant

15.2 Chemical safety assessment

For this product a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H411 Toxic to aquatic life with long lasting effects.
H302 Harmful if swallowed.
H412 Harmful to aquatic life with long lasting effects.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H304 May be fatal if swallowed and enters airways.

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ATE = acute toxicity estimate
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging
DMEL = Derived Minimum Effect Level
DNEL = Derived No Effect Level
EC50 = Median effective concentration
ECB = European Chemicals Bureau
EEC = European Economic Community
EINECS = European Inventory of Existing Commercial Chemical Substances
EL50 = Median effective loading
ELINCS = European List of Notified Chemical Substances
EmS = Emergency Schedules
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50 = Inhibition concentration, 50%
IMDG = International Maritime Code for Dangerous Goods
IUCLID = International Uniform Chemical Information Database
IVIS = In vitro irritation score
LC50 = Lethal concentration, 50%
LD50 = Median lethal dose
LC0 = lethal concentration, 0%
LOAEL = lowest-observed-adverse-effect level
LL50 = Median lethal loading
LQ = Limited Quantities
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration
PBT = Persistent, Bioaccumulative and Toxic substance
PNEC = Predicted No-Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
STP = Sewage Treatment Plant
TLV@TWA = Threshold limit value – time-weighted average
TLV@STEL = Threshold limit value – short-time exposure limit
VOC = Volatile Organic Compounds
vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Modified position none