



# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK  
REACH Regulation SI 2019/758

EVOLUTION FULL-TECH VSX 0W-20

SDS no. 086745  
:

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

**Product name** : EVOLUTION FULL-TECH VSX 0W-20  
**Product code** : 086745  
**Product description** : Not available.  
**Product type** : Liquid.  
**Other means of identification** : Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Identified uses

Engine oil

#### Uses advised against

Not applicable.

### 1.3 Details of the supplier of the safety data sheet

TotalEnergies Lubrifiants  
562 Avenue du Parc de L'île  
92029 Nanterre Cedex FRANCE  
Tél: +33 (0)1 41 35 40 00  
Fax: +33 (0)1 41 35 84 71  
rm.msds-lubs@totalenergies.com

H.S.E

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : National Poisons Information Service (NPIS): 111

#### Supplier

**Telephone number** : Emergency telephone: +44 1235 239670

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

**Ingredients of unknown ecotoxicity** : Contains 5.1% of components with unknown hazards to the aquatic environment

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements



## SECTION 2: Hazards identification

<b>Signal word</b>	: No signal word.
<b>Hazard statements</b>	: No hazard statement.
<b>Precautionary statements</b>	
<b>Prevention</b>	: Not applicable.
<b>Response</b>	: Not applicable.
<b>Storage</b>	: Not applicable.
<b>Disposal</b>	: Not applicable.
<b>Supplemental label elements</b>	: Contains C14-16-18 Alkyl phenol. May produce an allergic reaction. Safety data sheet available on request.
<b>Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles</b>	: Not applicable.

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration  $\geq 0,1$  %.

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

**Other hazards which do not result in classification** : Hazard of slipping on spilt product.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures** : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
Distillates (petroleum), hydrotreated heavy paraffinic	REACH #: 01-2119484627-25 EC: 265-157-1 CAS: 64742-54-7 Index: 649-467-00-8	$\geq 50 - \leq 75$	Asp. Tox. 1, H304	[1]
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	REACH #: 01-2119474878-16 EC: 276-737-9 CAS: 72623-86-0 Index: 649-482-00-X	$\leq 3$	Asp. Tox. 1, H304	[1]
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	REACH #: 01-2119474889-13 EC: 276-738-4 CAS: 72623-87-1 Index: 649-483-00-5	$\leq 3$	Asp. Tox. 1, H304	[1]
Distillates (petroleum), solvent-dewaxed heavy paraffinic	REACH #: 01-2119471299-27 EC: 265-169-7 CAS: 64742-65-0 Index: 649-474-00-6	$\leq 3$	Asp. Tox. 1, H304	[1]



## SECTION 3: Composition/information on ingredients

Distillates (petroleum), solvent-dewaxed light paraffinic	REACH #: 01-2119480132-48 EC: 265-159-2 CAS: 64742-56-9 Index: 649-469-00-9	≤3	Asp. Tox. 1, H304	[1]
Paraffin oils (petroleum), catalytic dewaxed heavy	REACH #: 01-2119487080-42 EC: 265-174-4 CAS: 64742-70-7	≤3	Asp. Tox. 1, H304	[1]
C14-16-18 Alkyl phenol	REACH #: 01-2119498288-19 EC: 931-468-2	≤0.3	Skin Sens. 1B, H317 STOT RE 2, H373  <b>See Section 16 for the full text of the H statements declared above.</b>	[1]

**Additional information** : Mineral oil of petroleum origin Product containing mineral oil with less than 3% DMSO extract as measured by IP 346 The product is made from synthetic base oils

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### Type

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
- Skin contact** : Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
dryness  
cracking



## SECTION 4: First aid measures

**Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous combustion products** : carbon monoxide  
carbon dioxide  
nitrogen oxides  
phosphorus oxides  
sulfur oxides  
Hydrogen sulfide  
Mercaptans  
Zinc oxides

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).



## SECTION 6: Accidental release measures

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8).  
See Section 10 for incompatible materials before handling or use.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

### 7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

No exposure limit value known.

#### Biological Limit Values (BLV)

No exposure indices known.

## SECTION 8: Exposure controls/personal protection

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**Advisory OEL** : Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m<sup>3</sup>, NIOSH (REL) TWA 5 mg/m<sup>3</sup>, STEL 10 mg/m<sup>3</sup>, ACGIH (TLV) TWA 5 mg/m<sup>3</sup> (highly refined)

### DNELs/DMELs

Product/substance	Type	Exposure	Value	Population	Effects
Distillates (petroleum), hydrotreated heavy paraffinic	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m <sup>3</sup>	Workers	Local
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	DNEL	Long term Inhalation	5.4 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Inhalation	1.2 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m <sup>3</sup>	General population	Local
OTHER LUBRICANT BASE OILS IP 346 < 3% w/w; Viscosity ≤ 20.5 mm <sup>2</sup> /s at 40°C	DNEL	Long term Inhalation	2.73 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Local
	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
Distillates (petroleum), solvent-dewaxed heavy paraffinic	DNEL	Long term Inhalation	1.19 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
	DNEL	Long term	1.19 mg/m <sup>3</sup>	General	Local



## SECTION 8: Exposure controls/personal protection

Distillates (petroleum), solvent-dewaxed light paraffinic	DNEL	Inhalation Long term	2.73 mg/m <sup>3</sup>	population Workers	Systemic
	DNEL	Inhalation Long term	5.58 mg/m <sup>3</sup>	Workers	Local
	DNEL	Inhalation Long term Oral	0.74 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m <sup>3</sup>	Workers	Systemic
Paraffin oils (petroleum), catalytic dewaxed heavy	DNEL	Long term Inhalation	5.58 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Oral	0.74 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m <sup>3</sup>	Workers	Local
C14-16-18 Alkyl phenol	DNEL	Long term Inhalation	1.17 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	0.3 mg/kg bw/day	Workers	Systemic

### PNECs

Product/substance	Compartment Detail	Value	Method Detail
Distillates (petroleum), hydrotreated heavy paraffinic	Secondary Poisoning	9.33 mg/kg	-
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Secondary Poisoning	9.33 mg/kg	-
C14-16-18 Alkyl phenol	Fresh water	0.1 mg/l	-
	Marine water	0.01 mg/l	-
	Fresh water sediment	4266.16 mg/kg	-
	dwt		
	Marine water sediment	426.62 mg/kg dwt	-
	Soil	852.58 mg/kg dwt	-
	Sewage Treatment Plant	100 mg/l	-

### 8.2 Exposure controls

**Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.



## SECTION 8: Exposure controls/personal protection

- Eye/face protection** : In case of contact through splashing: safety glasses with side-shields, EN 166.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Hydrocarbon-proof gloves  
nitrile rubber  
Fluorinated rubber
- Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
- In case of prolonged contact with the product, it is recommended to wear gloves complying with ISO 21420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency
- Body protection** : Wear work clothing with long sleeves.  
Non-skid safety shoes or boots
- Respiratory protection** : None under normal use conditions. If these are not sufficient to maintain exposure below the OEL, suitable respiratory protection must be worn (Type A/P1).
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature (20°C / 68°F) and pressure (1013 hPa) unless otherwise indicated

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid. [Clear]
- Colour** : blue green
- Odour** : Characteristic.
- Melting point/freezing point** : Technically not possible to measure
- Initial boiling point and boiling range** : >316°C (>600.8°F) [EN ISO 3405]
- Flammability (solid, gas)** : Not applicable.
- Upper/lower flammability or explosive limits** : Lower: 0.9%  
Upper: 7%
- Flash point** : Open cup: 230°C (446°F) [ASTM D 92]
- Auto-ignition temperature** : >230°C (>446°F) [ASTM E 659]
- Decomposition temperature** : Not applicable.
- pH** : Not applicable. Product is non-soluble (in water).
- Viscosity** : Dynamic (room temperature): Not available.  
Kinematic (room temperature): Not available.  
Kinematic (40°C): 41 mm<sup>2</sup>/s [EN ISO 3104]
- Solubility(ies)** :



## SECTION 9: Physical and chemical properties

Media	Result
water	Not soluble

- Miscible with water** : No.
- Partition coefficient: n-octanol/ water** : Not applicable.
- Vapour pressure** : <0.013 kPa (<0.1 mm Hg) [room temperature]  
Not applicable. [50°C (122°F)]
- Relative density** : 0.836 [ASTM D 4052]
- Density** : 0.836 g/cm<sup>3</sup> [15°C (59°F)] [ASTM D 4052]
- Vapour density** : >2 [Air = 1]
- Particle characteristics**
- Median particle size** : Not applicable.

### 9.2 Other information

- Pour point** : -66°C (-86.8°F)

## SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.
- 10.5 Incompatible materials** : Strong oxidising agents
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Product/substance	Result	Species	Dose	Exposure	Test
Distillates (petroleum), hydrotreated heavy paraffinic	LC50 Inhalation Dusts and mists	Rat - Male, Female	>5 mg/l	4 hours	OECD 403 Read across
	LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-	OECD 402 Read across
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-	OECD 401 Read across
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	LC50 Inhalation Dusts and mists	Rat	5.53 mg/l	4 hours	OECD 403



## SECTION 11: Toxicological information

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 401
	LC50 Inhalation Dusts and mists	Rat	5.1 mg/l	4 hours	OECD 403
Distillates (petroleum), solvent-dewaxed heavy paraffinic	LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-	Read across OECD 401
	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours	Read across OECD 403
Distillates (petroleum), solvent-dewaxed light paraffinic	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 420
	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours	OECD 403
Paraffin oils (petroleum), catalytic dewaxed heavy	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 401
	LC50 Inhalation Dusts and mists	Rat	5.1 mg/l	4 hours	-
	LC50 Inhalation Vapour	Rat	80.4 mg/l	1 hours	-
	LC50 Inhalation Vapour	Rat	20.1 mg/l	4 hours	-
	LD50 Dermal	Rabbit	>5000 mg/kg	-	-
C14-16-18 Alkyl phenol	LD50 Oral	Rat	>5000 mg/kg	-	-
	LD50 Dermal	Rat	2000 mg/kg	-	-
	LD50 Oral	Rat	2000 mg/kg	-	-

### Acute toxicity estimates

Product/substance	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	N/A	N/A	N/A	N/A	5.53
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	N/A	N/A	N/A	N/A	5.1
Paraffin oils (petroleum), catalytic dewaxed heavy	N/A	N/A	N/A	20.1	5.1

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Irritation/Corrosion

#### Conclusion/Summary

**Skin** : Based on available data, the classification criteria are not met.

**Eyes** : Based on available data, the classification criteria are not met.

**Respiratory** : Based on available data, the classification criteria are not met.

### Sensitisation

#### Conclusion/Summary

**Skin** : Based on available data, the classification criteria are not met. Contains sensitizer. May produce an allergic reaction.

**Respiratory** : Based on available data, the classification criteria are not met.

### Mutagenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Carcinogenicity



## SECTION 11: Toxicological information

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Reproductive toxicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Teratogenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Specific target organ toxicity (single exposure)

Not available.

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Specific target organ toxicity (repeated exposure)

Product/substance	Category	Route of exposure	Target organs
C14-16-18 Alkyl phenol	Category 2	-	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Aspiration hazard

Product/substance	Result
Distillates (petroleum), hydrotreated heavy paraffinic	ASPIRATION HAZARD - Category 1
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	ASPIRATION HAZARD - Category 1
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	ASPIRATION HAZARD - Category 1
Distillates (petroleum), solvent-dewaxed heavy paraffinic	ASPIRATION HAZARD - Category 1
Distillates (petroleum), solvent-dewaxed light paraffinic	ASPIRATION HAZARD - Category 1
Paraffin oils (petroleum), catalytic dewaxed heavy	ASPIRATION HAZARD - Category 1

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation.
- Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
dryness  
cracking
- Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure



## SECTION 11: Toxicological information

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**Conclusion/Summary** : Not available.

**General** : No known significant effects or critical hazards.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : No known significant effects or critical hazards.

## 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Product/substance	Result	Species	Exposure	Test
Distillates (petroleum), hydrotreated heavy paraffinic	Acute EC50 >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Acute EC50 >10000 mg/l	Crustaceans - <i>Daphnia magna</i>	48 hours	OECD 202
	Chronic NOEL >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Chronic NOEL >1000 mg/l	Crustaceans - <i>Daphnia magna</i>	21 days	-
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	Acute EL50 >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Acute EL50 >10000 mg/l	Crustaceans - <i>Daphnia magna</i>	48 hours	OECD 202
	Acute LL50 >1000 mg/l	Fish - <i>Pimephales promelas</i>	96 hours	OECD 203
	Chronic NOEL >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
Lubricating oils (petroleum),	Chronic NOEL >1000 mg/l	Crustaceans - <i>Daphnia magna</i>	21 days	OECD 211
	Acute EL50 >100 mg/l	Algae -	48 hours	OECD 201



## SECTION 12: Ecological information

C20-50, hydrotreated neutral oil-based	Acute EL50 >10000 mg/l	<i>Pseudokirchneriella subcapitata</i> Crustaceans - <i>Daphnia magna</i>	48 hours	OECD 202
	Acute LL50 >100 mg/l	Fish - <i>Pimephales promelas</i>	96 hours	OECD 203
	Chronic NOEL >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Chronic NOEL >1000 mg/l	Crustaceans - <i>Daphnia magna</i>	21 days	OECD 211
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Acute EL50 >10000 mg/l	Crustaceans - <i>Daphnia magna</i>	48 hours	OECD 202
	Acute LL50 >1000 mg/l	Fish - <i>Oncorhynchus mykiss</i>	96 hours	OECD 203
	Chronic NOEL >1000 mg/l	Crustaceans - <i>Daphnia magna</i>	21 days	OECD 211
Distillates (petroleum), solvent-dewaxed light paraffinic	Acute EL50 >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Acute EL50 10000 mg/l	Crustaceans - <i>Daphnia magna</i>	48 hours	OECD 202
	Acute EL50 ≥100 mg/l	Fish - <i>Pimephales promelas</i>	96 hours	OECD 203
	Chronic NOEL >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
Paraffin oils (petroleum), catalytic dewaxed heavy	Chronic NOEL >1000 mg/l	Crustaceans - <i>Daphnia magna</i>	21 days	OECD 211
	Acute EC50 10000 mg/l	Daphnia	48 hours	-
	Acute NOEL 101 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	-
C14-16-18 Alkyl phenol	Acute EC50 >100 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours	OECD 202

**Conclusion/Summary** : Not available.

### 12.2 Persistence and degradability

Product/substance	Test	Result	Dose	Inoculum
Distillates (petroleum), hydrotreated heavy paraffinic	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge
Distillates (petroleum), solvent-dewaxed heavy paraffinic	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge
Distillates (petroleum), solvent-dewaxed light paraffinic	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge

## SECTION 12: Ecological information

**Conclusion/Summary** : Not available.

Product/substance	Aquatic half-life	Photolysis	Biodegradability
Distillates (petroleum), hydrotreated heavy paraffinic	-	-	Not readily
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	-	-	Not readily
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	-	-	Not readily
Distillates (petroleum), solvent-dewaxed heavy paraffinic	-	-	Not readily
Distillates (petroleum), solvent-dewaxed light paraffinic	-	-	Not readily
Paraffin oils (petroleum), catalytic dewaxed heavy	-	-	Not readily

### 12.3 Bioaccumulative potential

Product/substance	LogP <sub>ow</sub>	BCF	Potential
Distillates (petroleum), hydrotreated heavy paraffinic	>4	-	High
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	6.1	-	High
Distillates (petroleum), solvent-dewaxed heavy paraffinic	9.2	260	Low
Distillates (petroleum), solvent-dewaxed light paraffinic	3.1	-	Low

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

**Mobility in soil** : Given its physical and chemical characteristics, the product generally shows low soil mobility. The product is insoluble and floats on water. Loss by evaporation is limited.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration  $\geq 0,1$  %.

### 12.6 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.



## SECTION 12: Ecological information

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.  
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used. The following Waste Codes are only suggestions: 13 02 05\*

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ICAO/IATA
<b>14.1 UN number or ID number</b>	Not regulated.	Not regulated.	Not regulated.	Not regulated.
<b>14.2 UN proper shipping name</b>	-	-	-	-
<b>14.3 Transport hazard class(es)</b>	-	-	-	-
<b>14.4 Packing group</b>	-	-	-	-
<b>14.5 Environmental hazards</b>	No.	No.	No.	No.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.



## SECTION 14: Transport information

**14.7 Maritime transport in bulk according to IMO instruments** : Not available.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
**UK (GB)/REACH**

**Annex XIV - List of substances subject to authorisation**

**Annex XIV**

None of the components are listed.

**Substances of very high concern**

None of the components are listed.

**Ozone depleting substances**

Not listed.

**Prior Informed Consent (PIC)**

Not listed.

**Persistent Organic Pollutants**

Not listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles**

**Seveso Directive**

This product is not controlled under the Seveso Directive.

**EU regulations**

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

**International regulations**

**Chemical Weapon Convention List Schedules I, II & III Chemicals**

Not listed.

**Montreal Protocol**

Not listed.

**Stockholm Convention on Persistent Organic Pollutants**

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)**



## SECTION 15: Regulatory information

Not listed.

### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### Inventory list

<b>Australia inventory (AIIC)</b>	: All components are listed or exempted.
<b>Canada inventory</b>	: All components are listed or exempted.
<b>China inventory (IECSC)</b>	: All components are listed or exempted.
<b>Europe inventory</b>	: All components are listed or exempted.
<b>Japan inventory</b>	: <b>Japan inventory (CSCL)</b> : All components are listed or exempted. <b>Japan inventory (ISHL)</b> : All components are listed or exempted.
<b>New Zealand Inventory of Chemicals (NZIoC)</b>	: All components are listed or exempted.
<b>Philippines inventory (PICCS)</b>	: All components are listed or exempted.
<b>Korea inventory (KECI)</b>	: All components are listed or exempted.
<b>Taiwan Chemical Substances Inventory (TCSI)</b>	: All components are listed or exempted.
<b>Thailand inventory</b>	: Not determined.
<b>Turkey inventory</b>	: Not determined.
<b>United States inventory (TSCA 8b)</b>	: All components are listed or exempted.
<b>Vietnam inventory</b>	: Not determined.

The information stated in this section relates solely to the conformity of the chemical product with the countries Inventories. The information used to confirm the inventory status of this product may be based on additional data to the chemical composition shown in Section 3. Other regulations may apply for importation or marketing authorizations.

**15.2 Chemical safety assessment** : Risk management measures and safety conditions of use are included in the relevant sections of the SDS

## SECTION 16: Other information

🔍 Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** :

- ACGIH = American Conference of Governmental Industrial Hygienists
- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- DNEL = Derived No Effect Level
- DMEL = Derived Minimal Effect Level
- DMSO = Dimethyl Sulfoxide
- EC50 = Half maximal effective concentration
- EL50 = median Effective Loading
- EUH statement = CLP-specific Hazard statement
- HSE = Health, Safety and Environment
- IC50 = Half maximal inhibitory concentration
- IDHL = Immediately dangerous to life or health
- LC50 = Median lethal concentration
- LD50 = Median lethal dose
- LL50 = median Lethal Loading
- LogKow = logarithm of the octanol/water partition coefficient
- N/A = Not available
- NIOSH = National Institute of Occupational Safety and Health



## SECTION 16: Other information

NOAEL = No Observed Adverse Effect Level  
NOEC No Observed Effect Concentration  
NOEL = No Observed Effect Level  
NOELR = No observed Effect Loading Rate  
OECD = Organisation for Economic Co-operation and Development  
OEL = Occupational Exposure Limit  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
QSAR = Quantitative Structure–Activity Relationship  
REL = Recommended Exposure Limit  
STEL = Short Term Exposure Limit  
TLV = Threshold Limit Value  
TWA = Time Weight Average  
VOC = Volatile Organic Compound  
vPvB = Very Persistent and Very Bioaccumulative  
Unique Formula Identifier (UFI)  
UVCB Substance of unknown or Variable composition, Complex reaction products or Biological material

### Procedure used to derive the classification

Not classified.

### Full text of abbreviated H statements

H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure.

### Full text of classifications

Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2

**Date of printing** : 2024/12/11

**Date of issue/ Date of revision** : 2024/12/11

**Date of previous issue** : No previous validation

**Version** : 1

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.