

Page 1 of 18
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 29.06.2018 / 0015
Replacing version dated / version: 18.05.2016 / 0014
Valid from: 29.06.2018
PDF print date: 02.07.2018
Cockpit Glanz XXL 600 mL
Art.: 1610

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Cockpit Glanz XXL 600 mL
Art.: 1610

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Car care
Sector of use [SU]:
SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites
SU21 - Consumer uses: Private households (=general public = consumers)
SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Chemical product category [PC]:
PC35 - Washing and cleaning products
Process category [PROC]:
PROC 7 - Industrial spraying
PROC10 - Roller application or brushing
PROC11 - Non industrial spraying
PROC19 - Manual activities involving hand contact
Article Categories [AC]:
AC99 - Not required.
Environmental Release Category [ERC]:
ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
ERC 8a - Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)
ERC 8d - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany
Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

| Hazard class | Hazard category | Hazard statement |
|--------------|-----------------|--|
| Aerosol | 1 | H222-Extremely flammable aerosol. |
| Asp. Tox. | 1 | H304-May be fatal if swallowed and enters airways. |

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 29.06.2018 / 0015
Replacing version dated / version: 18.05.2016 / 0014
Valid from: 29.06.2018
PDF print date: 02.07.2018
Cockpit Glanz XXL 600 mL
Art.: 1610

Aerosol

1

H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH066-Repeated exposure may cause skin dryness or cracking.

Without adequate ventilation, formation of explosive mixtures may be possible.

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substance

n.a.

3.2 Mixture

| Hydrocarbons, C11-C12, isoalkanes, <2% aromatics | |
|---|--|
| Registration number (REACH) | 01-2119472146-39-XXXX |
| Index | --- |
| EINECS, ELINCS, NLP | 918-167-1 (REACH-IT List-No.) |
| CAS | --- |
| content % | 10-<25 |
| Classification according to Regulation (EC) 1272/2008 (CLP) | Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 4, H413 |

| Ethanol | | Substance with specific conc. limit(s) acc. to REACH-registration |
|-----------------------------|--|---|
| Registration number (REACH) | | 01-2119457610-43-XXXX |
| Index | | 603-002-00-5 |
| EINECS, ELINCS, NLP | | 200-578-6 |
| CAS | | 64-17-5 |
| content % | | 1-5 |

Page 3 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.06.2018 / 0015
 Replacing version dated / version: 18.05.2016 / 0014
 Valid from: 29.06.2018
 PDF print date: 02.07.2018
 Cockpit Glanz XXL 600 mL
 Art.: 1610

Classification according to Regulation (EC) 1272/2008 (CLP)

Flam. Liq. 2, H225
 Eye Irrit. 2, H319

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
 The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
 Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
 Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.
 Keep Data Sheet available.

Ingestion

Call doctor immediately - have Data Sheet available.
 Do not induce vomiting.
 Danger of aspiration

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
 In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray
 CO2
 Extinction powder
 Foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:
 Oxides of carbon
 Toxic pyrolysis products.
 Danger of explosion by prolonged heating.
 Explosive vapour/air or gas/air mixtures.
 In case of spreading near the ground, flashback to distance sources of ignition is possible.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.
 Protective respirator with independent air supply.
 Cool container at risk with water.
 Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.06.2018 / 0015

Replacing version dated / version: 18.05.2016 / 0014

Valid from: 29.06.2018

PDF print date: 02.07.2018

Cockpit Glanz XXL 600 mL

Art.: 1610

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

Take explosion-prevention measures if applicable.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Do not use on hot surfaces.

Take precautions against electrostatic charges.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Observe special regulations for aerosols!

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

Observe special storage conditions.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters





Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):

1200 mg/m³

| (GB) | Chemical Name | Hydrocarbons, C11-C12, isoalkanes, <2% aromatics | Content %:10- <25 |
|------|--|--|----------------------|
| | WEL-TWA: 1200 mg/m ³ (>=C7 normal and branched chain alkanes) | WEL-STEL: 2(II) (AGW) | --- |
| | Monitoring procedures: | <ul style="list-style-type: none"> - Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174) | |

GB

Page 5 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.06.2018 / 0015
 Replacing version dated / version: 18.05.2016 / 0014
 Valid from: 29.06.2018
 PDF print date: 02.07.2018
 Cockpit Glanz XXL 600 mL
 Art.: 1610

| | | | |
|--|--|------------------------|--|
| BMGV: --- | | Other information: --- | |
|  Chemical Name | Ethanol | Content %:1-5 | |
| WEL-TWA: 1000 ppm (1920 mg/m3) | WEL-STEL: --- | --- | |
| Monitoring procedures: | <ul style="list-style-type: none">- Compur - KITA-104 SA (549 210)- Draeger - Alcohol 25/a Ethanol (81 01 631)- DFG (D) (Lösungsmittelgemische), Methode Nr. 6 DFG (E) (Solvent mixtures) - 1998,- 2002 - EU project BC/CEN/ENTR/000/2002-16 card 63-2 (2004) | | |
| BMGV: --- | | Other information: --- | |
|  Chemical Name | Butane | Content %: | |
| WEL-TWA: 600 ppm (1450 mg/m3) | WEL-STEL: 750 ppm (1810 mg/m3) | --- | |
| Monitoring procedures: | <ul style="list-style-type: none">- Compur - KITA-221 SA (549 459) | | |
| BMGV: --- | | Other information: --- | |
|  Chemical Name | Propane | Content %: | |
| WEL-TWA: 1000 ppm (ACGIH) | WEL-STEL: --- | --- | |
| Monitoring procedures: | <ul style="list-style-type: none">- Compur - KITA-125 SA (549 954) | | |
| BMGV: --- | | Other information: --- | |
|  Chemical Name | Isobutane | Content %: | |
| WEL-TWA: 1000 ppm (EX) (ACGIH) | WEL-STEL: --- | --- | |
| Monitoring procedures: | <ul style="list-style-type: none">- Compur - KITA-113 SB(C) (549 368) | | |
| BMGV: --- | | Other information: --- | |

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

| Ethanol | | | | | | |
|---------------------|--|-----------------------------|------------|-------|------------------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - freshwater | | PNEC | 0,96 | mg/l | |
| | Environment - marine | | PNEC | 0,79 | mg/l | |
| | Environment - water, sporadic (intermittent) release | | PNEC | 2,75 | mg/l | |
| | Environment - sewage treatment plant | | PNEC | 580 | mg/l | |
| | Environment - sediment, freshwater | | PNEC | 3,6 | mg/kg | |
| | Environment - soil | | PNEC | 0,63 | mg/kg dry weight | |
| | Environment - oral (animal feed) | | PNEC | 0,72 | mg/kg feed | |
| | Environment - sediment, marine | | PNEC | 2,9 | mg/kg dry weight | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 950 | mg/m3 | |
| Consumer | Human - dermal | Short term, local effects | DNEL | 950 | mg/m3 | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 114 | mg/m3 | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 87 | mg/kg | |

Page 6 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.06.2018 / 0015
 Replacing version dated / version: 18.05.2016 / 0014
 Valid from: 29.06.2018
 PDF print date: 02.07.2018
 Cockpit Glanz XXL 600 mL
 Art.: 1610

| | | | | | | |
|---------------------|--------------------|-----------------------------|------|------|------------|--|
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 206 | mg/kg bw/d | |
| Workers / employees | Human - inhalation | Short term, local effects | DNEL | 1900 | mg/m3 | |
| Workers / employees | Human - inhalation | Short term, local effects | DNEL | 950 | mg/m3 | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 343 | mg/kg bw/d | |

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. BS EN 14042.
 BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles (EN 166) with side protection, with danger of projections.

Skin protection - Hand protection:
 Protective nitrile gloves (EN 374)
 Minimum layer thickness in mm:
 0,4
 Permeation time (penetration time) in minutes:
 >480
 Protective hand cream recommended.
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
 Normally not necessary.
 If OES or MEL is exceeded.
 Gas mask filter A (EN 14387), code colour brown
 Gas mask filter AX (EN 14387), code colour brown.
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

Page 7 of 18
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 29.06.2018 / 0015
Replacing version dated / version: 18.05.2016 / 0014
Valid from: 29.06.2018
PDF print date: 02.07.2018
Cockpit Glanz XXL 600 mL
Art.: 1610

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|------------------------------------|
| Physical state: | Aerosol. Active substance: liquid. |
| Colour: | Colourless |
| Odour: | Characteristic |
| Odour threshold: | Not determined |
| pH-value: | Not determined |
| Melting point/freezing point: | Not determined |
| Initial boiling point and boiling range: | Not determined |
| Flash point: | n.a. |
| Evaporation rate: | Not determined |
| Flammability (solid, gas): | Not determined |
| Lower explosive limit: | 1,5 Vol-% |
| Upper explosive limit: | 8,5 Vol-% |
| Vapour pressure: | Not determined |
| Vapour density (air = 1): | Not determined |
| Density: | 0,632 g/ml |
| Bulk density: | Not determined |
| Solubility(ies): | Not determined |
| Water solubility: | Insoluble |
| Partition coefficient (n-octanol/water): | Not determined |
| Auto-ignition temperature: | 365 °C (Ignition temperature) |
| Decomposition temperature: | Not determined |
| Viscosity: | Not determined |
| Explosive properties: | Not determined |
| Oxidising properties: | Not determined |

9.2 Other information

| | |
|---------------------------|----------------|
| Miscibility: | Not determined |
| Fat solubility / solvent: | Not determined |
| Conductivity: | Not determined |
| Surface tension: | Not determined |
| Solvents content: | Not determined |

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Hazardous reactions will not occur during storage and handling under normal conditions.

10.4 Conditions to avoid

Pressure increase will result in danger of bursting.

Heating, open flame, ignition sources

Electrostatic charge

10.5 Incompatible materials

Avoid contact with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Cockpit Glanz XXL 600 mL

Art.: 1610

Page 8 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.06.2018 / 0015
 Replacing version dated / version: 18.05.2016 / 0014
 Valid from: 29.06.2018
 PDF print date: 02.07.2018
 Cockpit Glanz XXL 600 mL
 Art.: 1610

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|---|----------|-------|------|----------|-------------|--|
| Acute toxicity, by oral route: | | | | | | n.d.a. |
| Acute toxicity, by dermal route: | | | | | | n.d.a. |
| Acute toxicity, by inhalation: | | | | | | n.d.a. |
| Skin corrosion/irritation: | | | | | | n.d.a. |
| Serious eye damage/irritation: | | | | | | n.d.a. |
| Respiratory or skin sensitisation: | | | | | | n.d.a. |
| Germ cell mutagenicity: | | | | | | n.d.a. |
| Carcinogenicity: | | | | | | n.d.a. |
| Reproductive toxicity: | | | | | | n.d.a. |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | n.d.a. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | | n.d.a. |
| Aspiration hazard: | | | | | | n.d.a. |
| Symptoms: | | | | | | n.d.a. |
| Other information: | | | | | | Classification according to calculation procedure. |

| Hydrocarbons, C11-C12, isoalkanes, <2% aromatics | | | | | | |
|--|----------|-------|-------|----------|---|---|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | >5000 | mg/kg | Rabbit | OECD 427 (Skin Absorption - In Vivo Method) | |
| Acute toxicity, by inhalation: | LC50 | >5000 | mg/m3 | Rat | OECD 403 (Acute Inhalation Toxicity) | |
| Skin corrosion/irritation: | | | | | OECD 404 (Acute Dermal Irritation/Corrosion) | Mild irritant (Analogous conclusion), Repeated exposure may cause skin dryness or cracking. |
| Serious eye damage/irritation: | | | | | OECD 405 (Acute Eye Irritation/Corrosion) | Mild irritant (Analogous conclusion) |
| Respiratory or skin sensitisation: | | | | | OECD 406 (Skin Sensitisation) | No (skin contact), Analogous conclusion |
| Germ cell mutagenicity: | | | | | OECD 471 (Bacterial Reverse Mutation Test) | Negative, Analogous conclusion |
| Germ cell mutagenicity: | | | | | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative, Analogous conclusion |
| Germ cell mutagenicity: | | | | | OECD 474 (Mammalian Erythrocyte Micronucleus Test) | Negative, Analogous conclusion |
| Germ cell mutagenicity: | | | | | OECD 476 (In Vitro Mammalian Cell Gene Mutation Test) | Negative, Analogous conclusion |
| Germ cell mutagenicity: | | | | | OECD 478 (Genetic Toxicology - Rodent dominant Lethal Test) | Negative, Analogous conclusion |

Page 9 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.06.2018 / 0015
 Replacing version dated / version: 18.05.2016 / 0014
 Valid from: 29.06.2018
 PDF print date: 02.07.2018
 Cockpit Glanz XXL 600 mL
 Art.: 1610

| | | | | | | |
|---|--|--|--|--|--|--------------------------------|
| Germ cell mutagenicity: | | | | | OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells) | Negative, Analogous conclusion |
| Carcinogenicity: | | | | | OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies) | Analogous conclusion, Negative |
| Reproductive toxicity: | | | | | OECD 421 (Reproduction/Developmental Toxicity Screening Test) | Negative, Analogous conclusion |
| Reproductive toxicity: | | | | | OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developmental Tox. Screening Test) | Negative, Analogous conclusion |
| Reproductive toxicity: | | | | | OECD 414 (Prenatal Developmental Toxicity Study) | Negative, Analogous conclusion |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study) | Negative, Analogous conclusion |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developmental Tox. Screening Test) | Negative, Analogous conclusion |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) | Negative, Analogous conclusion |
| Aspiration hazard: | | | | | | Yes |
| Symptoms: | | | | | | drowsiness, headaches |

| Ethanol | | | | | | |
|------------------------------------|----------|-------|---------|------------------------|--|-------------------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | 10470 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | >2000 | mg/kg | Rabbit | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LC50 | 124,7 | mg/l/4h | Rat | OECD 403 (Acute Inhalation Toxicity) | |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Irritant |
| Respiratory or skin sensitisation: | | | | Mouse | OECD 429 (Skin Sensitisation - Local Lymph Node Assay) | No (skin contact) |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | Mouse | OECD 476 (In Vitro Mammalian Cell Gene Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative |

Page 10 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.06.2018 / 0015
 Replacing version dated / version: 18.05.2016 / 0014
 Valid from: 29.06.2018
 PDF print date: 02.07.2018
 Cockpit Glanz XXL 600 mL
 Art.: 1610

| | | | | | | |
|---|-------|-------|------------|-------------|--|--|
| Germ cell mutagenicity: | | | | | OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test) | Negative |
| Carcinogenicity: | NOAEL | >3000 | mg/kg | Rat | OECD 451 (Carcinogenicity Studies) | 24 mon |
| Reproductive toxicity: | NOAEL | 5200 | mg/kg bw/d | Rat | | |
| Specific target organ toxicity - repeated exposure (STOT-RE): | NOAL | >20 | mg/l | Rat | OECD 403 (Acute Inhalation Toxicity) | Male |
| Specific target organ toxicity - repeated exposure (STOT-RE): | NOAEL | 1730 | mg/kg/d | Rat | OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) | Female |
| Aspiration hazard: | | | | Human being | | No indications of such an effect. |
| Symptoms: | | | | | | respiratory distress, drowsiness, unconsciousness, drop in blood pressure, vomiting, coughing, headaches, intoxication, drowsiness, mucous membrane irritation, dizziness, nausea |
| Experiences in humans: | | | | | | Excessive alcohol consumption during pregnancy induces the foetus alcohol syndrome (reduced weight at birth, physical and mental disorders)., There is no sign that this syndrome is also caused by dermal or inhalative absorption. |

| Butane | | | | | | |
|--------------------------------|----------|-------|---------|----------|--|----------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by inhalation: | LC50 | 658 | mg/l/4h | Rat | | |
| Germ cell mutagenicity: | | | | | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Aspiration hazard: | | | | | | No |

Page 11 of 18
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 29.06.2018 / 0015
Replacing version dated / version: 18.05.2016 / 0014
Valid from: 29.06.2018
PDF print date: 02.07.2018
Cockpit Glanz XXL 600 mL
Art.: 1610

| | | | | | | |
|-----------|--|--|--|--|--|--|
| Symptoms: | | | | | | ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting. |
|-----------|--|--|--|--|--|--|

| Propane | | | | | | |
|---|----------|--------|---------|----------|--|--|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by inhalation: | LC50 | 658 | mg/l/4h | Rat | | |
| Germ cell mutagenicity: | | | | | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Reproductive toxicity (Developmental toxicity): | NOAEC | 21,641 | mg/l | | OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test) | |
| Aspiration hazard: | | | | | | No |
| Symptoms: | | | | | | breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting. |

| Isobutane | | | | | | |
|--------------------------------|----------|-------|---------|----------|--|--|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by inhalation: | LC50 | 658 | mg/l/4h | Rat | | |
| Serious eye damage/irritation: | | | | Rabbit | | Not irritant |
| Germ cell mutagenicity: | | | | | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Aspiration hazard: | | | | | | No |
| Symptoms: | | | | | | unconsciousness, frostbite, headaches, cramps, dizziness, nausea and vomiting. |

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

| Cockpit Glanz XXL 600 mL Art.: 1610 | | | | | | | |
|--|----------|------|-------|------|----------|-------------|--------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | | | | | | | n.d.a. |
| 12.1. Toxicity to daphnia: | | | | | | | n.d.a. |
| 12.1. Toxicity to algae: | | | | | | | n.d.a. |

Page 12 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.06.2018 / 0015
 Replacing version dated / version: 18.05.2016 / 0014
 Valid from: 29.06.2018
 PDF print date: 02.07.2018
 Cockpit Glanz XXL 600 mL
 Art.: 1610

| | | | | | | | |
|--|--|--|--|--|--|--|---|
| 12.2. Persistence and degradability: | | | | | | | n.d.a. |
| 12.3. Bioaccumulative potential: | | | | | | | n.d.a. |
| 12.4. Mobility in soil: | | | | | | | n.d.a. |
| 12.5. Results of PBT and vPvB assessment | | | | | | | n.d.a. |
| 12.6. Other adverse effects: | | | | | | | n.d.a. |
| Other information: | | | | | | | According to the recipe, contains no AOX. |

| Hydrocarbons, C11-C12, isoalkanes, <2% aromatics | | | | | | | |
|--|----------|------|-------|------|---------------------------------|--|-------------------------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | NOELR | 28d | 0,21 | mg/l | Oncorhynchus mykiss | QSAR | |
| 12.1. Toxicity to fish: | LL50 | 96h | >1000 | mg/l | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | EL50 | 48h | >1000 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to daphnia: | NOELR | 21d | 0,02 | mg/l | Daphnia magna | OECD 211 (Daphnia magna Reproduction Test) | |
| 12.1. Toxicity to algae: | ErL50 | 72h | >1000 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.1. Toxicity to algae: | EbL50 | 72h | >1000 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.1. Toxicity to algae: | NOELR | 72h | 1000 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | 28d | 31 | % | | OECD 301 F (Ready Biodegradability - Manometric Respirometry Test) | |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

| Ethanol | | | | | | | |
|----------------------------------|-----------|------|------------|------|---------------------|--------------------------------------|---|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.3. Bioaccumulative potential: | Log Pow | | -0,32 | | | | Bioaccumulation is unlikely (LogPow < 1). |
| 12.3. Bioaccumulative potential: | BCF | | 0,66 - 3,2 | | | | |
| 12.1. Toxicity to fish: | LC50 | 96h | 13000 | mg/l | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | LC50 | 48h | 12340 | mg/l | Daphnia magna | | |
| 12.1. Toxicity to daphnia: | NOEC/NOEL | | 9,6 | mg/l | Ceriodaphnia spec. | | |

Page 13 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.06.2018 / 0015
 Replacing version dated / version: 18.05.2016 / 0014
 Valid from: 29.06.2018
 PDF print date: 02.07.2018
 Cockpit Glanz XXL 600 mL
 Art.: 1610

| | | | | | | | |
|--|-----------|-----|----------|------|--------------------|--|-------------------------------------|
| 12.2. Persistence and degradability: | | | 97 | % | | OECD 301 B (Ready Biodegradability - Co2 Evolution Test) | Readily biodegradable |
| 12.1. Toxicity to algae: | EC50 | 72h | 275 | mg/l | Chlorella vulgaris | OECD 201 (Alga, Growth Inhibition Test) | |
| Other organisms: | NOEC/NOEL | | 280 | mg/l | Lemna gibba | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| 12.4. Mobility in soil: | H (Henry) | | 0,000138 | | | | |
| Toxicity to bacteria: | | | 440 | mg/l | | | |
| Other information: | COD | | 1,9 | g/g | | | |
| Other information: | BOD5 | | 1 | g/g | | | |

Butane

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|--|----------|------|-------|------|----------|-------------|---|
| 12.1. Toxicity to fish: | LC50 | 96h | 24,11 | mg/l | | QSAR | |
| 12.1. Toxicity to daphnia: | LC50 | 48h | 14,22 | mg/l | | QSAR | |
| 12.3. Bioaccumulative potential: | Log Pow | | 2,98 | | | | A notable biological accumulation potential is not to be expected (LogPow 1-3). |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

Propane

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|--|----------|------|-------|------|----------|-------------|---|
| 12.3. Bioaccumulative potential: | Log Pow | | 2,28 | | | | A notable biological accumulation potential is not to be expected (LogPow 1-3). |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

Isobutane

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|--|----------|------|-------|------|----------|-------------|---|
| 12.3. Bioaccumulative potential: | | | | | | | A notable biological accumulation potential is not to be expected (LogPow 1-3). |
| 12.1. Toxicity to fish: | LC50 | 96h | 27,98 | mg/l | | | |
| 12.1. Toxicity to algae: | EC50 | 96h | 7,71 | mg/l | | | |
| 12.2. Persistence and degradability: | | | | | | | Readily biodegradable |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 29.06.2018 / 0015
Replacing version dated / version: 18.05.2016 / 0014
Valid from: 29.06.2018
PDF print date: 02.07.2018
Cockpit Glanz XXL 600 mL
Art.: 1610

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

Do not dispose of with household waste.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

SECTION 14: Transport information

General statements

14.1. UN number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es):

2.1

14.4. Packing group:

-

Classification code:

5F

LQ:

1 L

14.5. Environmental hazards:

Not applicable

Tunnel restriction code:

D

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es):

2.1

14.4. Packing group:

-

EmS:

F-D, S-U

Marine Pollutant:

n.a

14.5. Environmental hazards:

Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es):

2.1

14.4. Packing group:

-

14.5. Environmental hazards:

Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.



SECTION 15: Regulatory information

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 29.06.2018 / 0015
Replacing version dated / version: 18.05.2016 / 0014
Valid from: 29.06.2018
PDF print date: 02.07.2018
Cockpit Glanz XXL 600 mL
Art.: 1610

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

| Hazard categories | Notes to Annex I | Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements | Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements |
|-------------------|------------------|---|---|
| P3a | 11.1 | 150 (netto) | 500 (netto) |

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

| Entry Nr | Dangerous substances | Notes to Annex I | Qualifying quantity (tonnes) for the application of - Lower-tier requirements | Qualifying quantity (tonnes) for the application of - Upper-tier requirements |
|----------|--|------------------|---|---|
| 18 | Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas | 19 | 50 | 200 |

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): ~ 90 %

50 - 100% III

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

4, 8, 15

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

| Classification in accordance with regulation (EC) No. 1272/2008 (CLP) | Evaluation method used |
|---|---|
| Aerosol 1, H222 | Classification according to calculation procedure. |
| Asp. Tox. 1, H304 | Classification according to calculation procedure. |
| Aerosol 1, H229 | Classification based on the form or physical state. |

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

Page 16 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.06.2018 / 0015
 Replacing version dated / version: 18.05.2016 / 0014
 Valid from: 29.06.2018
 PDF print date: 02.07.2018
 Cockpit Glanz XXL 600 mL
 Art.: 1610

H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H319 Causes serious eye irritation.
 H413 May cause long lasting harmful effects to aquatic life.

Aerosol — Aerosols
 Asp. Tox. — Aspiration hazard
 Flam. Liq. — Flammable liquid
 Aquatic Chronic — Hazardous to the aquatic environment - chronic
 Eye Irrit. — Eye irritation

Any abbreviations and acronyms used in this document:

AC Article Categories
 acc., acc. to according, according to
 ACGIH American Conference of Governmental Industrial Hygienists
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOEL Acceptable Operator Exposure Level
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
 BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)
 BMGV Biological monitoring guidance value (EH40, UK)
 BOD Biochemical oxygen demand
 BSEF Bromine Science and Environmental Forum
 bw body weight
 CAS Chemical Abstracts Service
 CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
 CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
 CIPAC Collaborative International Pesticides Analytical Council
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 COD Chemical oxygen demand
 CTFA Cosmetic, Toiletry, and Fragrance Association
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 DT50 Dwell Time - 50% reduction of start concentration
 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EC European Community
 ECHA European Chemicals Agency
 EEA European Economic Area
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ERC Environmental Release Categories
 ES Exposure scenario
 etc. et cetera
 EU European Union
 EWC European Waste Catalogue
 Fax. Fax number

Page 17 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 29.06.2018 / 0015
 Replacing version dated / version: 18.05.2016 / 0014
 Valid from: 29.06.2018
 PDF print date: 02.07.2018
 Cockpit Glanz XXL 600 mL
 Art.: 1610

gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 HET-CAM Hen's Egg Test - Chorionallantoic Membrane
 HGWP Halocarbon Global Warming Potential
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC Intermediate Bulk Container
 IBC (Code) International Bulk Chemical (Code)
 IC Inhibitory concentration
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 LC lethal concentration
 LC50 lethal concentration 50 percent kill
 LCLo lowest published lethal concentration
 LD Lethal Dose of a chemical
 LD50 Lethal Dose, 50% kill
 LDLo Lethal Dose Low
 LOAEL Lowest Observed Adverse Effect Level
 LOEC Lowest Observed Effect Concentration
 LOEL Lowest Observed Effect Level
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 NIOSH National Institute of Occupational Safety and Health (United States of America)
 NOAEC No Observed Adverse Effective Concentration
 NOAEL No Observed Adverse Effect Level
 NOEC No Observed Effect Concentration
 NOEL No Observed Effect Level
 ODP Ozone Depletion Potential
 OECD Organisation for Economic Co-operation and Development
 org. organic
 PAH polycyclic aromatic hydrocarbon
 PBT persistent, bioaccumulative and toxic
 PC Chemical product category
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 POCP Photochemical ozone creation potential
 ppm parts per million
 PROC Process category
 PTFE Polytetrafluorethylene
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
 SADT Self-Accelerating Decomposition Temperature
 SAR Structure Activity Relationship
 SU Sector of use
 SVHC Substances of Very High Concern
 Tel. Telephone
 ThOD Theoretical oxygen demand
 TOC Total organic carbon
 TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
 UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
 VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
 VOC Volatile organic compounds
 vPvB very persistent and very bioaccumulative

Page 18 of 18
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 29.06.2018 / 0015
Replacing version dated / version: 18.05.2016 / 0014
Valid from: 29.06.2018
PDF print date: 02.07.2018
Cockpit Glanz XXL 600 mL
Art.: 1610

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.