SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : E10 SHINE & GO SPRAY Product code : 58202

1.2. Relevant identified uses of the substance or mixture and uses advised against

Paint and varnish restorer

1.3. Details of the supplier of the safety data sheet

Registered company name : MOTUL Address : 119, Boulevard Felix Faure. 93300 AUBERVILLIERS CEDEX FRANCE Telephone : 33.1.48.11.70.00. Fax: 33.1.48.33.28.79. Telex: . Email : motul_hse@motul.fr

1.4. Emergency telephone number : +44 (0) 1235 239 670.

Association/Organisation : ORFILA.

🎾 🛛 Other emergency numbers

BRAZIL : +55 11 3197 5891 / COLOMBIA : +57 601 508 7337 / ARGENTINA : +54 11 5984 3690 / CHILE : +562 2582 9336 Ireland : +353 1 8092566 UNITED STATES: 001 866 928 0789 / CANADA: 001 800 579 7421 / MEXICO : +52 55 5004 8763 / MIDDLE EAST - AFRICA : +44 1235 239671 24 hours a day. Z days a week

24 hours a day, 7 days a week

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).

Skin irritation, Category 2 (Skin Irrit. 2, H315).

May produce an allergic reaction (EUH208).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

Hazardous to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411).

The propellant gas is taken into account when determining the health and environmental classification of the mixture.

2.2. Label elements

Mixture for aerosol application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



Signal Word : DANGER Product identifiers	5:	
EC 921-024-6		HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE
Additional labeling	g :	
EUH208		Contains (R)-P-MENTHA-1,8-DIENE. May produce an allergic reaction.
EUH208	Contains	. May
	LINALOOL	produce an
		allergic
		reaction.
EUH208		Contains CITRAL. May produce an allergic reaction.
EUH208		Contains GERANYL ACETATE. May produce an allergic reaction.
EUH208		Contains NERYL ACETATE. May produce an allergic reaction.
Hazard statement	ts :	
H222		Extremely flammable aerosol.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) E10 SHINE & GO SPRAY - 58202

0	SHINE & GO SPRAY - 58202	
	H229	Pressurised container: May burst if heated.
	H315	Causes skin irritation.
	H336	May cause drowsiness or dizziness.
	H411	Toxic to aquatic life with long lasting effects.
	Precautionary statements - G	eneral :
	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	Precautionary statements - Pr	revention :
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
		smoking.
	P211	Do not spray on an open flame or other ignition source.
	P251	Do not pierce or burn, even after use.
	P261	Avoid breathing spray.
	P271	Use only outdoors or in a well-ventilated area.
	P273	Avoid release to the environment.
	Precautionary statements - Re	esponse :
	P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P332 + P313	If skin irritation occurs: Get medical advice/attention.
	Precautionary statements - St	orage :
	P410 + P412	Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122 °F.
	Precautionary statements - Di	isposal :
	P501	Dispose of contents / container in accordance with local / regional / national /
		international regulations

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 59 of REACH: http://echa.europa.eu/fr/candidate-list-table The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006. The mixture does not contain substances> = 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	Classification (EC) 1272/2008	Note	%
INDEX: 103175/10	GHS02	[i]	50 <= x % < 100
CAS: 106-97-8	Dgr		
EC: 203-448-7	Flam. Gas 1A, H220		
REACH: 01-2119474691-32	Press. Gas, H280		
BUTANE			
INDEX: 103175/2	GHS07, GHS09, GHS08, GHS02		10 <= x % < 25
EC: 921-024-6	Dgr		
REACH: 01-2119475514-35	Flam. Liq. 2, H225		
	Asp. Tox. 1, H304		
HYDROCARBONS, C6-C7, N-ALKANES,	Skin Irrit. 2, H315		
ISOALKANES, CYCLICS, <5%	STOT SE 3, H336		
N-HEXANE	Aquatic Chronic 2, H411		
INDEX: 103175/11	GHS02	[i]	10 <= x % < 25
CAS: 74-98-6	Dgr		
EC: 200-827-9	Flam. Gas 1A, H220		
REACH: 01-2119486944-21	Press. Gas, H280		
PROPANE			
INDEX: 103175/12	GHS02	(i)	2.5 <= x % < 10
CAS: 75-28-5	Dgr		
EC: 200-857-2	Flam. Gas 1A, H220		
REACH: 01-2119485395-27	Press. Gas, H280		
ISOBUTANE			
INDEX: 103175/3	GHS07, GHS09, GHS08, GHS02	[i]	0 <= x % < 1
CAS: 5989-27-5	Dgr		

Liq. 3, H226 Fox. 1, H304 rrit. 2, H315 Sens. 1, H317 ic Acute 1, H400 ute = 1 ic Chronic 1, H410 ronic = 1 GHS07	
GHS07	
Wng Skin Irrit. 2, H315 Skin Sens. 1B, H317 Eye Irrit. 2, H319	0 <= x % < 1
7 rrit. 2, H315 Sens. 1, H317 rit. 2, H319	[i] 0 <= x % < 1
17 rrit. 2, H315 Sens. 1B, H317 ic Chronic 3, H412	0 <= x % < 1
	0 <= x % < 1
	07 Irrit. 2, H315 Sens. 1B, H317 atic Chronic 3, H412

Specific concentration limits:

Identification	Specific concentration limits	ATE		
INDEX: 103175/4		oral: ATE = 2790		
CAS: 78-70-6		mg/kg BW		
EC: 201-134-4				
REACH:				
01-2119474016-42				
LINALOOL				

Information on ingredients :

(Full text of H-phrases: see section 16)

[i] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of an allergic reaction, seek medical attention.

Apply resuscitation techniques. Prolonged clinical monitoring may be necessary.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

In the event of splashes or contact with skin :

C2

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner. Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated aera is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

- In the event of a fire, use :
- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder

- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO2)

5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

Spilled product may make surfaces slippery.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

Do not get in eyes, on skin, or on clothing.

Spray in short bursts, without prolonged spraying.

Follow standard health and safety rules on account of flammability.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Take precautionary measures against static discharges by bonding and grounding equipment.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Avoid inhaling vapors.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Ensure good ventilation at the workplace

Keep in original container. Do not pierce of burn, even after usage.

Storage and handling instructions applicable to pressurised gases.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

Do not breathe fumes, vapour, spray.

Avoid high temperatures

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
106-97-8	1000 ppm					
74-98-6	1000 ppm					
75-28-5	1000 ppm					
5392-40-5	5 (IFV) ppm			Skin; SEN; A4		
- Germany	- AGW (BAuA - TRG	S 900, 02/2022) :				
CAS	VME :	VME :	Excess	Notes		
106-97-8		1000 ppm		4(II)		
		2400 mg/m3				
74-98-6		1000 ppm		4(II)		
		1800 mg/m3				
75-28-5		1000 ppm		4(II)		
		2400 mg/m3				
5989-27-5		5 ppm		4(II)		
		28 mg/m3				
- France (I	NRS - Outils 65 / 202	1-1849, 2021-1763, de	cree of 09/12/2021):		
CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
106-97-8	800	1900				
- UK / WEI	(Workplace exposure	e limits, EH40/2005, F	ourth Edition 2020)	:		
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
106-97-8	600 ppm	750 ppm		Carc		

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction.

Personnel shall wear regularly laundered overalls.

1450 mg/m3

C

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

1810 mg/m3

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVA (Polyvinyl alcohol)

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact. Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

Respiratory protection

Avoid inhaling vapors.

If the ventilation is insufficient, wear appropriate breathing apparatus.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) E10 SHINE & GO SPRAY - 58202

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device. Type of FFP mask :

Wear a disposable half-mask aerosol filter in accordance with standard EN149/A1.

Category :

- FFP1

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

Particle filter according to standard EN143 :

- P1 (White)

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

\sim	Physical state	
1	Physical state :	Fluid liquid.
-		Spray.
2	Colour	
	Unspecified	
\sim	Odour	
1	Odour threshold :	Not stated.
2	Melting point	
1	Melting point/melting range :	Not relevant.
2	Freezing point	
1	Freezing point / Freezing range :	Not stated.
2	Boiling point or initial boiling point and boiling range	
1	Boiling point/boiling range :	65 °C.
\sim	Flammability	00 0.
	Flammability (solid, gas) :	Not stated.
\sim	Lower and upper explosion limit	Not Stateu.
	Explosive properties, lower explosivity limit (%) :	Not stated.
	Explosive properties, lower explosivity limit (%) :	Not stated.
	Flash point	Not stated.
	Flash point interval :	Not relevant.
\sim		Not relevant.
	Auto-ignition temperature	200 °C.
2	Self-ignition temperature :	200 C.
	Decomposition temperature Decomposition point/decomposition range :	200 °C.
a		200 C.
2	pH	
	pH :	Not relevant. Not stated.
2	pH (aqueous solution) : Kinematic viscosity	Not Stated.
	-	Not stated.
2	Viscosity : Solubility	Not stated.
1	-	Incolubio
	Water solubility : Fat solubility :	Insoluble. Not stated.
\sim	Partition coefficient n-octanol/water (log value)	Not Stateu.
	Partition coefficient: n-octanol/water :	Not stated.
2		Not stated.
	Vapour pressure Vapour pressure (50°C) :	Nat valovont
a		Not relevant.
2	Density and/or relative density	
2	Density :	<1
	Relative vapour density	
2	Vapour density :	Not stated.
\sim	Particle characteristics	
2.	The mixture does not contain nanoforms.	
7	9.2. Other information	

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

役 🛛 Aerosols

Chemical combustion heat :

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

>= 30 kJ/q.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating
- heat
- humidity
- accumulation of electrostatic charges.
- flames and hot surfaces

10.5. Incompatible materials

- Keep away from :
- water
- strong acids
- oxidising agents

10.6. Hazardous decomposition products

- The thermal decomposition may release/form :
- carbon monoxide (CO)
- carbon dioxide (CO2)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness. May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

11.1.1. Substances

Acute toxicity :

LINALOOL Oral route :

LD50 = 2790 mg/kg bodyweight/day

(CAS: 78-7

Version 5.1 (18-06-2024) - Page 8/11

11.1.2. Mixture

Respiratory or skin sensitisation :

Contains at least one sensitising substance. May cause an allergic reaction.

11.2. Information on other hazards

Endocrine disrupting properties

The mixture does not contain any substance evaluated as an endocrine disruptor with effects on human health.

Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 5989-27-5 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

SECTION 12 : ECOLOGICAL INFORMATION Toxic to aquatic life with long lasting effects. The product must not be allowed to run into drains or waterways. 12.1. Toxicity 12.1.2. Mixtures 12.2. Persistence and degradability 12.2.1. Substances I INALOOL Biodegradability : no degradability data is available, the substance is considered as not degrading quickly. 12.2.2. Mixtures Biodegradation : No data on decomposition is available, the mixture is not considered to decompose rapidly. 12.3. Bioaccumulative potential No data available. 12.4. Mobility in soil Not very mobile in soil. The product is insoluble in water and will spread on the surface 12.5. Results of PBT and vPvB assessment No data available. 12.6. Endocrine disrupting properties The mixture does not contain any substance evaluated as an endocrine disruptor with environmental effects.

12.7. Other adverse effects

Do not dispose of the product in the natural environment, effluents or surface waters.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container. Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2023 - IMDG 2022 [41-22] - ICAO/IATA 2024 [65]).

14.1. UN number or ID number

1950

14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

14.3. Transport hazard class(es)

- Classification :

(CAS: 78-7



14.4. Packing group

. . .

14.5. Environmental hazards

- Environmentally hazardous material :



14.6. Special precautions for user

-	•										
ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel	
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D	
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregati on		
	2	See SP63	-	See SP277	F-D. S-U	63 190 277 327 344 381 959	E0	- SW1 SW22	SG69		
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ		
	2.1	-	-	Forbidden	Forbidden	203	150 kg	A1 A145 A167 A802	E0		
	2.1	-	-	Forbidden	Forbidden	-	-	A1 A145 A167 A802	E0		

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG. For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG. Marine pollutant (IMDG 3.1.2.9):(hydrocarbons, c6-c7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Classification and labelling information included in section 2:

- The following regulations have been used:
 - EU Regulation No. 1272/2008 amended by EU Regulation No. 2023/707.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2024/197. (ATP 21)

Container information:

No data available.

Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH): https://echa.europa.eu/substances-restricted-under-reach.

Explosives precursors :

The mixture does not contain any substance subject to Regulation (EU) 2019/1148 on the marketing and use of explosives precursors.

Particular provisions :

Total net weight of the aerosol (active 244 g

product + gas) :

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of

knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE : Acute Toxicity Estimate

BW : Body Weight

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

GHS09 : Environment

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.