

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

* 1.1. Product identifier

Trade name/designation:

RAVENOL OTC Premix -40°C Protect C12+

Article No.:

1410112

UFI:

MWY5-XSQN-GFGR-89GM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Antifreeze agent

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

Ravensberger Schmierstoffvertrieb GmbH

Jöllenbecker Str. 2 33824 Werther Germany

Telephone: +49 5203 9719 0
Telefax: +49 5203 9719 40
E-mail: kontakt@ravenol.de
Website: www.ravenol.de

E-mail (competent person): technik@ravenol.de

1.4. Emergency telephone number

Abt. Technik (Produktsicherheit), 24h: +49 700 24 112 112 (Company ID: RAV) (outside USA/Canada) 011 49 700 24 112 112 (Company ID: RAV) (inside USA/Canada), +49 5203 9719 0 (Mo-Do 7.30 Uhr - 16.30 Uhr, Fr 7.30 Uhr - 13.15 Uhr) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]:

Hazard classes and hazard categories	Hazard statements	Classification pro cedure
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	Calculation method.
STOT-repeated exposure (STOT RE 2)	H373: May cause damage to organs through prolonged or repeated exposure. (May cause damage to kidneys if swallowed.)	Calculation method.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:





GHS07 Exclamation mark

GHS08 Health hazard

Signal word: Warning

Hazard components for labelling:

potassium 2-ethylhexanoate; ethane-1,2-diol



hazard statements for health hazards		
H319	Causes serious eye irritation.	
H373	May cause damage to organs through prolonged or repeated exposure. (May cause damage to kidneys if swallowed.)	

Supplemental hazard information: -

Precautionary statements		
P101	If medical advice is needed, have product container or label at hand.	
P102	102 Keep out of reach of children.	

Precautionary statements Prevention		
P260	Do not breathe dust/fume/gas/mist/vapours/spray.	
P264	Wash hands thoroughly after handling.	
P280	Wear eye/face protection.	

Precautionary statements Response		
P305 + P351 + P338	+ IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P314	Get medical advice/attention if you feel unwell.	
P337 + P313	If eye irritation persists: Get medical advice/attention.	

Precautionary statements Disposal		
P501	Dispose of contents/container to an appropriate recycling or disposal facility.	

2.3. Other hazards

Other adverse effects:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition / information on ingredients

* │ 3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concen- tration
CAS No.: 107-21-1 EC No.: 203-473-3	ethane-1,2-diol Acute Tox. 4, STOT RE 2 Warning H302-H373	30 - < 60 weight-%
CAS No.: 3164-85-0 EC No.: 221-625-7	potassium 2-ethylhexanoate Eye Dam. 1, Repr. 2, Skin Irrit. 2 H315-H318-H361d	0 – < 2 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing. If unconscious but breathing normally, place in recovery position and seek medical advice. Do not leave affected person unattended.

Following inhalation:

In case of respiratory tract irritation, consult a physician. Provide fresh air. Get immediate medical advice/attention.

In case of skin contact:

In case of skin irritation, consult a physician. After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse.

After eye contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Causes serious eye irritation.



Following ingestion:

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. If unconscious but breathing normally, place in recovery position and seek medical advice. Harmful if swallowed. May cause damage to organs.(kidneys)

Self-protection of the first aider:

First aider: Pay attention to self-protection! Use personal protection equipment. No direct artificial respiration to be given by first aider.

4.2. Most important symptoms and effects, both acute and delayed

Reference to other sections: SECTION 2: Hazards identification SECTION 11: Toxicological information

4.3. Indication of any immediate medical attention and special treatment needed

Observe risk of aspiration if vomiting occurs. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam Carbon dioxide (CO2)

Extinguishing powder

Use water spray jet to protect personnel and to cool endangered containers.

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Gases/vapours, toxic. The product itself does not burn.

Hazardous combustion products:

Nitrogen oxides (NOx) Carbon monoxide Carbon dioxide (CO2)

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

5.4. Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Use personal protection equipment. Special danger of slipping by leaking/spilling product. Do not breathe vapour.

Protective equipment:

Wear protective gloves/protective clothing/eye protection/face protection.

Emergency procedures:

Eliminate all ignition sources if safe to do so. Remove persons to safety. Provide adequate ventilation.

6.1.2. For emergency responders

Personal protection equipment:

Use appropriate respiratory protection.

6.2. Environmental precautions

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Immediately inform the responsible authorities in entry into waterways or sewage system.

6.3. Methods and material for containment and cleaning up

For containment:

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

RAVENOL OTC Premix -40°C Protect C12+

Revision date: 19 May 2021 Version: 5 Print date: 20 May 2021



Other information:

Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

SECTION 7: Handling and storage

SECTION 8: Exposure controls/personal protection

SECTION 13: Disposal considerations

6.5. Additional information

Clear spills immediately.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Harmful if swallowed. Do not breathe gas/vapour. Keep out of reach of children. Wash hands before breaks and after work.

Fire prevent measures:

No special fire protection measures are necessary.

Measures to prevent aerosol and dust generation:

Provide adequate ventilation.

Environmental precautions:

See section 8.

Advices on general occupational hygiene

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. When using do not eat, drink, smoke, sniff. Remove contaminated, saturated clothing.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep locked up and out of reach of children.

Requirements for storage rooms and vessels:

Keep/Store only in original container. Shafts and sewers must be protected from entry of the product.

Hints on storage assembly:

Do not store together with: Food and feedingstuffs

Storage class (TRGS 510, Germany): 12 – non-combustible liquids that cannot be assigned to any of the above storage classes

Further information on storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

Recommendation:

Observe technical data sheet.

Antifreeze / Coolant



SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

CAS No.: 107-21-1 EC No.: 203-473-3 BE	Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
CAS No.: 107-21-1 EC No.: 203-473-3 (3 40 ppm (104 mg/m²) (6 (Aérosol, peut être absorbé par la peau)	СН		
CAS No.: 107-21-1 (2) 38.8 ppm (100 mg/m²) (5) (môže pronikat pokožkou)	BE	CAS No.: 107-21-1	③ 40 ppm (104 mg/m³)
CAS No.: 107-21-1 25 mg/m³ (może przenikać przez skórę do organizmu)	CZ	CAS No.: 107-21-1	② 38.8 ppm (100 mg/m³)
CAS No.: 107-21-1 EC No.: 203-473-3 2 40 ppm (104 mg/m³) (kan absorberes gjennom huden)	PL	CAS No.: 107-21-1	② 50 mg/m³
CAS No.: 107-21-1 C No.: 203-473-3 (2) 20 ppm (52 mg/m³) (3) (Aerosol und Dampf, kann über die Haut aufgenommen wirden) (3) 20 ppm (52 mg/m³) (2) 40 ppm (104 mg/m²) (2) 40 ppm (104 mg/m²) (3) 40 ppm (100 mg/m³) (4) 40 ppm (55 mg/m³) (4) 40 ppm (55 mg/m³) (4) 40 ppm (50 mg/m³) (4) 40 ppm (50 mg/m³) (4) 40 ppm (104 mg/m³	NO	CAS No.: 107-21-1	② 40 ppm (104 mg/m³)
CAS No.: 107-21-1 EC No.: 203-473-3 (2) 40 ppm (104 mg/m³) (3) (may be absorbed through the skin) MY ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3 HTP (FI) ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3 (2) 40 ppm (100 mg/m³) (2) 40 ppm (100 mg/m³) (3) 39.4 ppm (100 mg/m³) (4) ppm (100 mg/m³) (5) (kan absorberas genom huden) LT ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3 EC No.: 20	TRGS 900 (DE)	CAS No.: 107-21-1	 2 20 ppm (52 mg/m³) (S) (Aerosol und Dampf, kann über die Haut aufgenommen we
CAS No.: 107-21-1 EC No.: 203-473-3 HTP (FI) ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	IE	CAS No.: 107-21-1	② 40 ppm (104 mg/m³)
CAS No.: 107-21-1 EC No.: 203-473-3 ② 40 ppm (100 mg/m³) ⑤ (kan absorberas genom huden) LT ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3 ② 20 ppm (50 mg/m³) ⑥ (garų ir Aerozolis) (tikėtinas įsisavinimas per odą) Šis RD to komas bendrai garu ir aerozolio koncentracijai. SE ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3 PEL (SK) MAK (AT) ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3 DK ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3 ② 20 mg/m³ ② 20 mg/m³ ② 20 ppm (52 mg/m³)	MY	CAS No.: 107-21-1	③ 39.4 ppm (100 mg/m³)
CAS No.: 107-21-1 EC No.: 203-473-3 © 20 ppm (50 mg/m³) ⑤ (garų ir Aerozolis) (tikėtinas įsisavinimas per odą) Šis RD to komas bendrai garu ir aerozolio koncentracijai. SE ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3 DK ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3 Q 20 ppm (52 mg/m³) Q 20 ppm (52 mg/m³)	HTP (FI)	CAS No.: 107-21-1	② 40 ppm (100 mg/m³)
CAS No.: 107-21-1 EC No.: 203-473-3 ② 40 ppm (104 mg/m³) ③ (kan absorberas genom huden) NPEL (SK) ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3 DK ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3 ② 40 ppm (104 mg/m³) ② 40 ppm (104 mg/m³) ③ (rátajte so vstrebávaním cez pokožku) ① 10 ppm (26 mg/m³) ② 20 mg/m³ ② 20 mg/m³ ② 20 ppm (52 mg/m³)	ப	CAS No.: 107-21-1	 2 20 ppm (50 mg/m³) (5) (garų ir Aerozolis) (tikėtinas įsisavinimas per odą) Šis RD tai
CAS No.: 107-21-1 EC No.: 203-473-3 ② 40 ppm (104 mg/m³) ⑤ (rátajte so vstrebávaním cez pokožku) MAK (AT) ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3 DK ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3 ② 20 ppm (26 mg/m³) ② 20 ppm (52 mg/m³)	SE	CAS No.: 107-21-1	② 40 ppm (104 mg/m³)
CAS No.: 107-21-1 EC No.: 203-473-3 DK ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3 20 ppm (52 mg/m³)	NPEL (SK)	CAS No.: 107-21-1	② 40 ppm (104 mg/m³)
CAS No.: 107-21-1 EC No.: 203-473-3 DK ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3 ① 10 ppm (26 mg/m³) ② 20 ppm (52 mg/m³)	MAK (AT)	CAS No.: 107-21-1	
CAS No.: 107-21-1 ② 20 ppm (52 mg/m³)		CAS No.: 107-21-1 EC No.: 203-473-3	② 20 mg/m³
1	DK	CAS No.: 107-21-1	② 20 ppm (52 mg/m³)



Limit value	Substance name	① Long-term occupational exposure limit value
type (country of origin)		② short-term occupational exposure limit value
o. og,		③ Instantaneous value
		Monitoring and observation processes
DAAL (AT)		S Remark
MAK (AT)	ethane-1,2-diol CAS No.: 107-21-1	② 20 ppm (52 mg/m³)
	EC No.: 203-473-3	(\$) (max. 8x5 min./Schicht, Momentanwert, kann über die Haut aufgenommen werden)
BG	ethane-1,2-diol	① 20 ppm (52 mg/m³)
	CAS No.: 107-21-1	② 40 ppm (104 mg/m³)
	EC No.: 203-473-3	(5) (трябва да се очаква абсорбиране през кожата)
HR	ethane-1,2-diol	① 20 ppm (52 mg/m³)
	CAS No.: 107-21-1 EC No.: 203-473-3	② 40 ppm (104 mg/m³)
	EC No.: 203-473-3	⑤ (mora se uzeti u obzir prodiranje kroz kožu)
ES	ethane-1,2-diol	① 20 ppm (52 mg/m³)
	CAS No.: 107-21-1 EC No.: 203-473-3	② 40 ppm (104 mg/m³)
		⑤ (puede ser absorbido a través dérmica)
RO	ethane-1,2-diol CAS No.: 107-21-1	① 20 ppm (52 mg/m³)
	EC No.: 203-473-3	② 40 ppm (104 mg/m³)
	12 11	(§) (e de asteptat asimilarea prin piele)
EE	ethane-1,2-diol CAS No.: 107-21-1	① 20 ppm (52 mg/m³)
	EC No.: 203-473-3	 ② 40 ppm (104 mg/m³) ⑤ (naha kaudu kergesti absorbeeruvad ained, aur ja Aerosool)
LV	ethane-1,2-diol	① 20 ppm (52 mg/m³)
LV	CAS No.: 107-21-1	② 40 ppm (104 mg/m³)
	EC No.: 203-473-3	(\$ (var absorbet caur adu)
Alberta (CA)	ethane-1,2-diol	③ 100 mg/m³
	CAS No.: 107-21-1 EC No.: 203-473-3	© 100 mg/m
BC (CA)	ethane-1,2-diol CAS No.: 107-21-1	③ 100 mg/m³
	EC No.: 203-473-3	(\$) (Aerosol)
BC (CA)	ethane-1,2-diol	① 10 mg/m³
	CAS No.: 107-21-1 EC No.: 203-473-3	② 20 mg/m³
		⑤ (particles)
BC (CA)	ethane-1,2-diol CAS No.: 107-21-1	③ 50 mg/m³
	EC No.: 203-473-3	⑤ (vapor)
IOELV (EU)	ethane-1,2-diol	① 20 ppm (52 mg/m³)
	CAS No.: 107-21-1 EC No.: 203-473-3	② 40 ppm (104 mg/m³)
		⑤ (may be absorbed through the skin)
VRI (FR)	ethane-1,2-diol CAS No.: 107-21-1	① 20 ppm (52 mg/m³)
	EC No.: 203-473-3	② 40 ppm (104 mg/m³)
WEL (CD)		(5) (peut être absorbé par la peau)
WEL (GB)	ethane-1,2-diol CAS No.: 107-21-1	① 20 ppm (52 mg/m³) ② 40 ppm (104 mg/m³)
	EC No.: 203-473-3	(3) (vapour, may be absorbed through the skin)
SI	ethane-1,2-diol	① 20 ppm (52 mg/m³)
	CAS No.: 107-21-1	② 40 ppm (104 mg/m³)
	EC No.: 203-473-3	(s) (računati je treba z možnostjo prodiranja skozi kožo)
TW	ethane-1,2-diol	① 10 mg/m³
	CAS No.: 107-21-1	⑤ (蒸汽)
TW	EC No.: 203-473-3 ethane-1,2-diol	(3) 50 ppm (127 mg/m³)
. • •	CAS No.: 107-21-1	③ 50 ppm (127 mg/m³) ⑤ (霧)
	EC No.: 203-473-3	₩ (375)

ра

RAVENOL

Revision date: 19 May 2021 Version: 5 Print date: 20 May 2021

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
WEL (GB)	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	① 10 mg/m³ ⑤ (may be absorbed through the skin)
KR	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	(③ 40 ppm (100 mg/m³) (⑤ (증기 와(과) 연무)
IS	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	 10 ppm (26 mg/m³) 40 ppm (104 mg/m³) (efnið getur auðveldlega borist inn í líkamann gegnum húð)
IS	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	 ① 10 ppm (26 mg/m³) ⑤ (úðaefni, efnið getur auðveldlega borist inn í líkamann gegnum húð)
CN	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 mg/m³ ② 40 mg/m³
HU	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	 ① 52 mg/m³ ② 104 mg/m³ ⑤ (felvehető a bőrön keresztül)
RU	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	① 5 mg/m³ ③ 10 mg/m³
GR	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	① 50 ppm (125 mg/m³) ② 50 ppm (125 mg/m³)
NL	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	① 52 mg/m³ ② 104 mg/m³ ⑤ (damp)
ACGIH (US)	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	② 10 mg/m³ ⑤ (inhalable fraction Aerosol)
NL	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	① 10 mg/m³ ⑤ (deeltjes)
TR	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	 20 ppm (52 mg/m³) 40 ppm (104 mg/m³) (cilt yoluyla alınabilir)
ACGIH (US)	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	① 25 ppm ② 50 ppm ⑤ (vapor)
Québec (CA)	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	③ 50 ppm (127 mg/m³)

8.1.2. Biological limit values

No data available

RAVENOL

Revision date: 19 May 2021 **Version:** 5 **Print date:** 20 May 2021

8.1.3. DNEL-/PNEC-values

ра

Substance name	DNEL value	① DNEL type
		② Exposure route
ethane-1,2-diol CAS No.: 107-21-1	35 mg/m³	① DNEL worker ② Long-term – inhalation, local effects
EC No.: 203-473-3		© Long-term - minaration, local effects
ethane-1,2-diol	7 mg/m ³	① DNEL worker
CAS No.: 107-21-1 EC No.: 203-473-3		② Long-term – inhalation, local effects
ethane-1,2-diol	106 mg/kg	① DNEL worker
CAS No.: 107-21-1 EC No.: 203-473-3		② Long-term - dermal, systemic effects
ethane-1,2-diol	53 mg/kg	① DNEL Consumer
CAS No.: 107-21-1 EC No.: 203-473-3		② Long-term - dermal, systemic effects
potassium 2-ethylhexanoate	32 mg/m³	① DNEL worker
CAS No.: 3164-85-0 EC No.: 221-625-7		② Long-term – inhalation, systemic effects
potassium 2-ethylhexanoate	8 mg/m ³	① DNEL Consumer
CAS No.: 3164-85-0 EC No.: 221-625-7		② Long-term – inhalation, systemic effects
potassium 2-ethylhexanoate	12 mg/kg	① DNEL worker
CAS No.: 3164-85-0 EC No.: 221-625-7		② Long-term - dermal, systemic effects
potassium 2-ethylhexanoate	6 mg/kg	① DNEL Consumer
CAS No.: 3164-85-0 EC No.: 221-625-7		② Long-term - dermal, systemic effects
potassium 2-ethylhexanoate	2.5 mg/kg	① DNEL Consumer
CAS No.: 3164-85-0 EC No.: 221-625-7		② Long-term - oral, systemic effects

Substance name	PNEC Value	① PNEC type
ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	10 mg/l	① PNEC aquatic, freshwater
ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	1 mg/l	① PNEC aquatic, marine water
ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	199.5 mg/l	① PNEC sewage treatment plant
ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	37 mg/kg	① PNEC sediment, freshwater
ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	3.7 mg/kg	① PNEC sediment, marine water
ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	1.53 mg/kg	① PNEC soil
ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	10 mg/l	① PNEC aquatic, intermittent release
potassium 2-ethylhexanoate CAS No.: 3164-85-0 EC No.: 221-625-7	0.36 mg/l	① PNEC aquatic, freshwater
potassium 2-ethylhexanoate CAS No.: 3164-85-0 EC No.: 221-625-7	0.036 mg/l	① PNEC aquatic, marine water
potassium 2-ethylhexanoate CAS No.: 3164-85-0 EC No.: 221-625-7	71.7 mg/l	① PNEC sewage treatment plant
potassium 2-ethylhexanoate CAS No.: 3164-85-0 EC No.: 221-625-7	6.37 mg/kg	① PNEC sediment, freshwater

RAVENOL OTC Premix -40°C Protect C12+

Revision date: 19 May 2021 Version: 5 Print date: 20 May 2021



Substance name	PNEC Value	① PNEC type
potassium 2-ethylhexanoate CAS No.: 3164-85-0 EC No.: 221-625-7	0.637 mg/kg	① PNEC sediment, marine water
potassium 2-ethylhexanoate CAS No.: 3164-85-0 EC No.: 221-625-7	1.06 mg/kg	① PNEC soil
potassium 2-ethylhexanoate CAS No.: 3164-85-0 EC No.: 221-625-7	0.493 mg/l	① PNEC aquatic, intermittent release

8.2. Exposure controls

8.2.1. Appropriate engineering controls

See section 7. No additional measures necessary.

8.2.2. Personal protection equipment





Eye/face protection:

During transfer: Eye glasses with side protection

DIN-/EN-Norms DIN EN 166

Skin protection:

Hand protection

Suitable material: NBR (Nitrile rubber), PVC (polyvinyl chloride), CR (polychloroprene, chloroprene

ubber)

Thickness of the glove material: >= 0,3 mm

Breakthrough time: 480 min

Breakthrough times and swelling properties of the material must be taken into consideration.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Tested protective gloves must be worn: EN ISO 374

Suitable protective clothing: Protective clothing **Respiratory protection:**

Usually no personal respirative protection necessary.

Thermal hazards:

No data available.

Other protection measures:

Wash hands before breaks and after work.

8.2.3. Environmental exposure controls

See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid Colour: violet

Odour: characteristic

Safety relevant basis data

parameter		at °C	Method	Remark
рН	8	20 °C		
Melting point	not determined			
Freezing point	< -40 °C			
Initial boiling point and boiling	not determined			
range				
Decomposition temperature	not determined			
Flash point	not determined			
Evaporation rate	not determined			

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Page 10/15

RAVENOL OTC Premix -40°C Protect C12+

Revision date: 19 May 2021 Version: 5 Print date: 20 May 2021



parameter		at °C	Method	Remark
Auto-ignition temperature	not determined			
Upper/lower flammability or explosive limits	not determined			
Vapour pressure	not determined			
Vapour density	not determined			
Density	1,070 kg/m³	20 °C		
Relative density	not determined			
Bulk density	not determined			
Water solubility	completely miscible			
Partition coefficient: n-octanol/ water	not determined			
Dynamic viscosity	not determined			
Kinematic viscosity	not determined			

9.2. Other information

Not applicable.

SECTION 10: Stability and reactivity

10.1. Reactivity

No known hazardous reactions. hygroscopic.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

responds with: Oxidising agent, strong, Strong acid

10.4. Conditions to avoid

To avoid thermal decomposition do not overheat.

10.5. Incompatible materials

Oxidising agent, strong

Acid, concentrated

10.6. Hazardous decomposition products

The product is stable under storage at normal ambient temperatures.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Substance name	Toxicological information
ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	LD ₅₀ oral: 1,600 mg/kg (cATpE:) LD ₅₀ dermal: >3,500 mg/kg LC ₅₀ Acute inhalation toxicity (vapour): >2.5 mg/l LC ₅₀ Acute inhalation toxicity (gas): >2.5 mg/l 6 h
potassium 2-ethylhexanoate CAS No.: 3164-85-0 EC No.: 221-625-7	LD ₅₀ oral: 2,043 mg/kg (Rat) LD ₅₀ dermal: >2,000 mg/kg (Rat)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

No irritant effect. Frequently or prolonged contact with skin may cause dermal irritation.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

RAVENOL OTC Premix -40°C Protect C12+

Revision date: 19 May 2021 Version: 5 Print date: 20 May 2021



Page 11/15

Serious eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation:

No sensitizing effects known.

Germ cell mutagenicity:

No indications of human germ cell mutagenicity exist.

Carcinogenicity:

No indication of human carcinogenicity.

Reproductive toxicity:

No indications of human reproductive toxicity exist.

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

May cause damage to kidneys through prolonged or repeated exposure if swallowed.

Aspiration hazard:

Observe risk of aspiration if vomiting occurs.

Additional information:

Data apply to the main component.

ethanediol

st ullet 11.2. Information on other hazards

Endocrine disrupting properties:

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1. Toxicity

Substance name	Toxicological information
ethane-1,2-diol	LC ₅₀ : 72,860 mg/l
CAS No.: 107-21-1 EC No.: 203-473-3	EC₅₀: >100 mg/l
LC No.: 203-473-3	NOEC: 8,590 mg/l
	NOEC: 15,380 mg/l
	EC ₅₀ : 46,300 mg/l
	LC ₅₀ : 14 - 18 mg/l
	LC ₅₀ : 41,000 mg/l
potassium 2-ethylhexanoate	LC ₅₀ : >100 mg/l 4 d (fish, Oryzias latipes (Ricefish))
CAS No.: 3164-85-0 EC No.: 221-625-7	EC₅₀: 910 mg/l 2 d (crustaceans, Daphnia magna (Big water flea))
	EC₅₀: 49.3 mg/l 3 d (Algae/water plant, Desmodesmus subspicatus)
	LC ₅₀ : >100 mg/l
	EC ₅₀ : 910 mg/l
	NOEC: 25 mg/l

Assessment/classification:

The substance/mixture does not fullfill the criteria of the acute aquatic toxicity according to Regulation (EC) No 1272/2008 [CLP], Annex I.

Additional ecotoxicological information:

The information about ecology refers to the main components.

* 12.2. Persistence and degradability

Substance name	Biodegradation	Remark
ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	Yes, rapidly	
potassium 2-ethylhexanoate CAS No.: 3164-85-0 EC No.: 221-625-7	Yes, rapidly	OECD Guideline 107

Biodegradation:

Readily biodegradable. Data apply to the main component.

RAVENOL OTC Premix -40°C Protect C12+

Revision date: 19 May 2021 Version: 5 Print date: 20 May 2021



Additional information:

The product has not been tested.

12.3. Bioaccumulative potential

Substance name	Log K _{OW}	Bioconcentration factor (BCF)
ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	-1.36	
potassium 2-ethylhexanoate CAS No.: 3164-85-0 EC No.: 221-625-7	2.96	

Accumulation / Evaluation:

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

$f * \mid f 12.5.$ Results of PBT and vPvB assessment

Substance name	Results of PBT and vPvB assessment
ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	The substance in the mixture does not meet the PBT/ vPvB criteria according to REACH, annex XIII.
potassium 2-ethylhexanoate CAS No.: 3164-85-0 EC No.: 221-625-7	The substance in the mixture does not meet the PBT/ vPvB criteria according to REACH, annex XIII.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

* 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste according to applicable legislation.

Waste treatment options

Appropriate disposal / Product:

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal.

Appropriate disposal / Package:

Non-contaminated packages may be recycled.

13.2. Additional information

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

No dangerous good in sense of these transport regulations.

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO- TI / IATA-DGR)	
14.1. UN number o	ID number			
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	
14.2. UN proper shipping name				
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	



Land transport (ADR/ RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO- TI / IATA-DGR)
14.3. Transport haz	ard class(es)		
not relevant			
14.4. Packing group)		
not relevant			
14.5. Environmenta	l hazards		
not relevant			
14.6. Special preca	utions for user		
not relevant			_

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Restrictions on use:

Use restriction according to REACH annex XVII, no.: ethanediol

Other regulations (EU):

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]: This product is not assigned to a hazard category.

15.1.2. National regulations

[DE] National regulations

Restrictions of occupation

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Störfallverordnung

for substances contained in the product:

This product is not assigned to a hazard category.

Water hazard class

WGK:

1 - schwach wassergefährdend

Source:

Self-classification (mixture; calculation rule).

Technische Regeln für Gefahrstoffe

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

Berufsgenossenschaftliche Vorschriften (DGUV-Vorschriften)

Berufsgenossenschaftliche Informationen (DGUV-Informationen) 868 Berufsgenossenschaftliche Regeln (DGUV-Regeln) 189, 190, 192, 195

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

15.3. Additional information

Tactile warning according to EN/ISO 11683. Child-resistant fastenings (EN/862/ISO 8317).



SECTION 16: Other information

16.1. Indication of changes

1.1.	Product identifier
2.1.	Classification of the substance or mixture
2.2.	Label elements
3.2.	Mixtures
8.1.	Control parameters
9.1.	Information on basic physical and chemical properties
11.1.	Information on hazard classes as defined in Regulation (EC) No 1272/2008
11.2.	Information on other hazards
12.1.	Toxicity
12.2.	Persistence and degradability
12.5.	Results of PBT and vPvB assessment
12.6.	Endocrine disrupting properties
15.1.	Safety, health and environmental regulations/legislation specific for the substance or mixture
16.1.	Indication of changes

16.2. Abbreviations and acronyms

See overview table at www.euphrac.eu

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

16.3. Key literature references and sources for data

67/548/EEC - Dangerous Substances Directive 1999/45/EEC - Dangerous Preparations Directive EC 1907/2006 - REACH Regulation 1272/2008 EC - Regulation on classification, labeling and packaging of substances and mixtures, and amending Directives 67/548/EEC and 1999/45/EC and Regulation (EC) No 1907/2006 Regulation (EC) No 1907/2006 (REACH), Annex II European Chemicals Agency (ECHA), C & L classification and labeling inventory European Chemicals Agency (ECHA), ECHA CHEM Registered substances OECD The Global Portal to Information on Chemical Substances (ChemPortal) Institute for Occupational Safety and Health of the German Social Accident Insurance (IFA): GESTIS substance database and International limit values for chemical substances Federal Environment Agency, Section IV 2.4: Documentation and Information Centre substances hazardous to water Rigoletto (catalog substances hazardous to water)

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Classification according to Regulation (EC) No 1272/2008 [CLP]:

Hazard classes and hazard categories	Hazard statements	Classification pro cedure
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	Calculation method.
STOT-repeated exposure (STOT RE 2)	H373: May cause damage to organs through prolonged or repeated exposure. (May cause damage to kidneys if swallowed.)	Calculation method.

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements	
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure. ()

16.6. Training advice

No data available



16.7. Additional information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

* Data changed compared with the previous version